

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION  
P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

5a. Indicate Type of Lease  
State ☒ Fee ☐  
5. State Oil & Gas Lease No.  
B-4120-1

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name -
2. Name of Operator TEXACO Inc.	8. Farm or Lease Name New Mexico 'AH' State
3. Address of Operator P. O. Box 728, Hobbs, New Mexico 88240	9. Well No. 13
4. Location of Well UNIT LETTER E, 2080 FEET FROM THE North LINE AND 989 FEET FROM THE WEST LINE, SECTION 8, TOWNSHIP 17-S, RANGE 36-E, NMPM.	10. Field and Pool, or Wildcat Undesignated
15. Elevation (Show whether DF, RT, GR, etc.) 3896' (GR)	12. County

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TOTAL DEPTH 5200'  
20" OD 94# J-55 CSG (CONDUCTOR PIPE) SET @ 310'  
13 3/8" OD 54# K-55 CSG SET @ 1950'.

1. Ran 5165' (121 jts.) 5 5/8" OD 24# 832#S-80&J-55 Csg & set @ 5200'.
2. Cemented 1st stage W/400 sx. Howco Lite Cement containing 5# gilsonite, 8# salt, & .5 CFR-2 per sack. Followed W/600 sx. class 'H' cement containing 8# salt, & .5 CFR-2 per sack.
3. With DV Tool open @ 2946' cemented 2nd stage W/850 sx. Howco lite Cement containing 8# salt per sack. Followed W/200 sx. class 'H' Cement. Cement did not circulate. Top of cement 1300' by temperature survey. Job complete 6:30 PM, 6-17-83. WOC in excess of 18 hrs.
4. Tested 8 5/8" csg to 1500# for 30 minutes, 3:00-3:30 PM, 6-18-83. Tested OK. Job complete 3:30 PM, 6-18-83.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE Asst. Dist. Mgr. DATE 6-21-83

ORIGINAL SIGNED BY JERRY SEXTON

APPROVED BY DISTRICT 1 SUPERVISOR TITLE DATE JUN 24 1983

CONDITIONS OF APPROVAL, IF ANY: