

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

5a. Indicate Type of Lease
State ☒ Fee ☐
5. State Oil & Gas Lease No.
K-2875

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Fred G. Yates, Inc.	8. Farm or Lease Name "GO" State
3. Address of Operator Security Nat'l Bank Bldg, Suite 919, Roswell, New Mexico 88201	9. Well No. 1
4. Location of Well UNIT LETTER <u>A</u> <u>460</u> FEET FROM THE <u>North</u> LINE AND <u>990</u> FEET FROM THE <u>East</u> LINE, SECTION <u>13</u> TOWNSHIP <u>19S</u> RANGE <u>34E</u> NMPM.	10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 3942.9' GR	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

5/25/83 Dresser Atlas ran Neutron Density, DLL-MLL logs and took 25 sidewall cores. Decision made to P & A. RU Halliburton and placed 35 sx cmt plug #1 @ 5700' - 5800' and placed 35 sx cmt plug #2 @ 5000' - 5100' 1 1/2 hrs, LD drill pipe - 1 1/4 hrs and trip 7 1/4 hrs.

5/26/83 Halliburton placed abandonment cement plug #3 35 sx cmt @ 3500' - 3600', and plug #4 45 sx cmt @ 1990' - 1865'. Rig released @ 12 noon 5/25/83.

5/27/83 Installed regulation dryhole marker in 10 sx cmt plug @ surface. Fenced reserve pit.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED John R. McMinn TITLE John R. McMinn, Engineer DATE June 22, 1983

APPROVED BY Lyle F. Turnacliff TITLE OIL & GAS INSPECTOR DATE MAY 9 - 1986

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

JUN 23 1983

**O.C.D.
HOBBS OFFICE**