

## OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-133  
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.B.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
K-2875	

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Fred G. Yates, Inc.	8. Farm or Lease Name "GO" State
3. Address of Operator Security Nat'l Bank Bldg., Ste 919, Roswell, New Mexico 88201	9. Well No. 1
4. Location of Well UNIT LETTER <u>A</u> <u>460</u> FEET FROM THE <u>North</u> LINE AND <u>990</u> FEET FROM THE <u>East</u> LINE, SECTION <u>13</u> TOWNSHIP <u>19S</u> RANGE <u>34E</u> NMPM.	10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 3942.9' GR	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

## NOTICE OF INTENTION TO:

## SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐PLUG AND ABANDON ☐  
CHANGE PLANS ☐OTHER ☐REMEDIAL WORK ☐  
COMMENCE DRILLING OPNS. ☒  
CASING TEST AND CEMENT JOBS ☐ALTERING CASING ☐  
PLUG AND ABANDONMENT ☐OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

5/7/83 RU Young Drilling Company Rig #5. Spudded 12 1/4" hole at 7:30 p.m. 5/6/83. Depth 760'. Deviation 3/4° @ 451'.

5/8/83 Depth 1700'. Deviation 3 1/2° @ 1196', 2 1/2° @ 1305', 1 3/4° @ 1633'.

5/9/83 Depth 1872'. Ran 46 jts new 8 5/8" 24# J-55 ST&C 8 round csg w/guide shoe and automatic fill float insert on top of bottom jt. Cmt'd w/700 sx Halliburton Lite and 200 sx neat. Top of top plug in 8 5/8" csg - 1829'. Deviation 3/4° @ 1872'.

5/10/83 Depth 2825'. Deviation survey: 1° @ 2402'.

5/11/83 Depth 3369'. Placed 120 sx cement to plug back through open ended DP from 2400' to 2890' due to crooked hole. Deviation Survey: 1° @ 2405'; 3° @ 2908'; 4 1/4° @ 2994'; 3 3/4° @ 3088'; 5° @ 3304'; 5 1/2° @ 3365'.

5/12/83 Re-drlg @ 2866'. Re-drilling, after cmt plug back, in an attempt to straighten hole. Re-drill deviation survey: 1° @ 2770'; 2° @ 2835'; 2 1/2° @ 2866'.

5/13/83 PBTD on second cement plug - 2730'. Drilled into original hole below cement plug #1. Re-plugged from 2730' to 3050'.

5/14/83 Original hole 3369'. Second re-drill - depth 2824'. Re-drilling and reaming to straighten hole.

5/15/83 Depth 2942'. Deviation Survey: 1 1/2° @ 2845', 1 1/2° @ 2876' and 2° @ 2935'.

5/16/83 Depth 3553'. Deviation Survey: 2° @ 3337' and 2° @ 3427'.

CONTINUED

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED John R. McMinn TITLE John R. McMinn, Engineer DATE May 31, 1983ORIGINAL SIGNED BY JERRY SEXTON  
DISTRICT 1 SUPERVISOR

JUN 6 1983

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

JUN 3 1983

O.C.D.  
HOBBS OFFICE

5/17/83 Depth 4121'. Deviation Survey: 1 1/4° @ 3584', 1° @ 3928',  
5/18/83 Depth 4372'. Deviation Survey: 2 3/4° @ 4158', 1 1/2° @ 4267',  
5/20/83 Depth 4980'. Deviation Survey: 1/2° @ 4763',  
5/24/83 TD 5800'. Deviation Survey: 1° @ 5800'.