

Submit 3 Copies To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 South First, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised March 25, 1999

OIL CONSERVATION DIVISION
2040 South Pacheco
Santa Fe, NM 87505

4. Well No.	30-025-28239
5. Indicate Type of Lease	STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.	LG-6977
7. Lease Name or Unit Agreement Name:	Aztec Dos State
8. Well No.	#1
9. Pool name or Wildcat	Young Bone Spring, N.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
Oil Well ☒ Gas Well ☐ Other ☐
2. Name of Operator
Lynx Petroleum Consultants, Inc.
3. Address of Operator
P.O. Box 1708 Hobbs, NM 88241
4. Well Location

Unit Letter L : 2080 feet from the South line and 660 feet from the West line
Section 2 Township 18S Range 32E NMPM County Lea

10. Elevation (Show whether DR, RKB, RT, GR, etc.)
3871.6' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

- PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
- TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
- PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐
- OTHER: ☐

SUBSEQUENT REPORT OF:

- REMEDIAL WORK ☐ ALTERING CASING ☐
- COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
- CASING TEST AND CEMENT JOB ☐
- OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

1. Set a C.I.B.P. @ 8250' and dump bail 35' of cement or spot 25 sxs cement on top of C.I.B.P. - **TAG BOTTOM PLUG**
 2. Set a C.I.B.P. @ 6600' and dump bail 35' of cement or spot 25 sxs cement on top of C.I.B.P.
 3. Circulate the hole with 9.5 ppg brine gel mud.
 4. Cut and pull the 4 1/2" casing at 4540'.
 5. Spot 50 sxs cement plug 4440'-4590'. Tag plug.
 6. Spot 30 sxs cement plug 600'-705'. - **TAG PLUG (CSG. SHOE)**
 7. Spot 10 sxs cement surface plug.
 8. Cut off wellhead and anchors. Install dryhole marker. Clear location.
- SPOT 25 SX PLUG T.O.S. F/1250'-1150'

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Marc Wise TITLE President DATE 1/16/01
Type or print name Marc Wise Telephone No. 392-6950
(This space for State use)

APPROVED BY _____ TITLE _____ DATE _____

Conditions of approval, if any:

NOTICE TO THE PUBLIC
PLUGGING OPERATIONS FOR OIL & GAS
TO BE APPROVED.

do