

PROPOSED PLUG AND ABANDONMENT  
1/12/01

Elev. 3872' GR +13' KB

SPOT 10 SXS CEMENT SURFACE PLUG

SPOT 30 SXS CEMENT PLUG 600'-705'

653' - 13 3/8", H-40, 48# Casing  
Cemented w/750 sxs. Circulated to Surf.

SPOT 50 SXS CEMENT PLUG 4440'-4590'

4490' - 8 5/8", J-55, 32# & 24# Casing.  
Cemented w/1600 sxs. Circulated to Surf.

CUT AND PULL 4 1/2" CASING AT 4540'

T.O.C. @ 4680' (Cement Bond Log)

MUD

DUMP BAIL 35' OF CEMENT OR SPOT 25 SXS ON C.I.B.P.

SET A C.I.B.P. @ 6600'

Perfs 6668'-6736' (68' Overall)

DUMP BAIL 35' OF CEMENT OR SPOT 25 SXS ON C.I.B.P.

SET A C.I.B.P. @ 8250'

Perfs 8302'-8518' (216' Overall)

8637' - 4 1/2", 11.6# & 10.5#  
Cemented w/950 sxs

T.D. @ 8640'

LYNX PETROLEUM

Aztec Dos State #1

2080' FSL & 660' FWL

Sec. 2, T-18S, R-32E

Lea County, N.M.