

Form 9-331  
Dec. 1973

Form Approved.  
Budget Bureau No. 42-R1424

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

RECEIVED

JAN 19 10 19 1984

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐  
well well other

2. NAME OF OPERATOR  
Superior Oil Company, The

3. ADDRESS OF OPERATOR  
P.O. Box 3901, Midland, TX 79702

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 660 FSL & 660 FWL of Section 10  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

☐  
☐  
☒  
☐  
☐  
☐  
☐  
☐

5. LEASE

ANNO-0554858

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

NGMT

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Government 10

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Scharb (Bone Spring)

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 10, T-19S, R35E

12. COUNTY OR PARISH

Lea

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3795.9' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

1. MI & RU on 11-17-83. Set Retrieval B.P. @ 9290'.
2. Perf additional Bone Springs interval 9010-9022 (13 holes) 9038-9068 (31 holes) 9106-9159 (54 holes).
3. Acidize 9010'-9159' w/6000 gal 15% HCL acid.
4. Acidize 9010'-9159' w/90,000 gal 20% gelled acid.
5. GIH w/pumping assembly and put on pump TA @ 8893' w/1-1/4 pump.
6. On Production 12-1-83.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

ACCEPTED FOR RECORD

TITLE Division Opr. Supt.

DATE

1-17-84

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL

MAY 9 1984

Carlsbad,

NEW MEXICO

\*See Instructions on Reverse Side

RECEIVED  
MAY 11 1984  
O.C.D.  
HOBBS OFFICE