

N. M. OIL CONS. COMMISSION
P. O. BOX 1980
HOBBS, NEW MEXICO 88240

Form 9-331
Dec. 1973

Form Approved.
Budget Bureau No. 42-R1424

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐
well well other

2. NAME OF OPERATOR

Harvey E. Yates Company

3. ADDRESS OF OPERATOR

P. O. Box 1933, Roswell, New Mexico 88201

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 2080' FSL & 1980' FWL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

PULL OR ALTER CASING

MULTIPLE COMPLETE

CHANGE ZONES

ABANDON*

(other)

SUBSEQUENT REPORT OF:

5. LEASE
NM-11118

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Young Deep Unit

8. FARM OR LEASE NAME

9. WELL NO.

10.

10. FIELD OR WILDCAT NAME

N. Young Bonespring

11. SEC. T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 3, T-18S, R-32E

12. COUNTY OR PARISH 13. STATE

Lea NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3871.4

(NOTE: Report results of multiple completion or depth change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1/22/84 Cont Drlg out to 6930'. Tested Perfs @ 6863' to 6925' to 1500 psi for 15" - O.K. Cont drlg out D.V. tool to 8208'.
1/24/84 New PBTD 9002'.
1/25/84 GIH w/Geo Source & Perf B Sp sd @ 8737', 39', 41'; 8770' & 8772'; 8780', 85', 88', 99', & 8801'.
1/26/84 Acidize w/2500 gal 7 1/2% SRA w/22 ball sealers & 2% kcl flush.
1/31/84 Frac w/60,000 gal WF 40 w/3% HCL & 1/3 CO2.
2/04/84 Well flwd 100-200#. Had 350 Bbls in tank. Turn well over to production.

Subsurface Safety Valve: Manu. and Type

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Ray J. [Signature] TITLE Reservoir Engineer DATE February 8, 1984

ACCEPTED FOR RECORD (This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL IF ANY

MAY 11 1984

RECEIVED
MAY 15 1984
FBI - NEW YORK

RECEIVED
MAY 15 1984
FBI - NEW YORK
FBI OFFICE