

AL 11.01.1983  
P. O. Box 1933  
Roswell, NM 88201

Form Approved  
Budget Bureau No. 42-R1424

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

RECEIVED

DEC 29 10 35 AM '83

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.

1. oil well ☒ gas well ☐ other ☐
2. NAME OF OPERATOR  
Harvey E. Yates Company
3. ADDRESS OF OPERATOR  
P. O. Box 1933, Roswell, NM 88201
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE 1200' FSL & 1650' FEL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH. Same
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

5. LEASE  
NM-036852
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME  
Young Deep 3 Federal
9. WELL NO.  
#4
10. FIELD OR WILDCAT NAME  
Wildcat
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 3, T-18S, R-32E
12. COUNTY OR PARISH: 13. STATE  
Lea NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3878.8' GR

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) Spud & Run. Csg ☐

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

(NOTE: Report results of multiple completion or zone change on Form 9-333.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

12/03/83 Spudded 10:45 a.m. 12/2/83. Ran 17 jts 13 3/8" csg, set @ 664', cmt w/250 sxs HOWCO lite, 1/4# floceal, 2% CaCl & 350 sx Cl "C" w/2% CaCl. WOC 18 hrs Tst w/1000 psi - held ok.

12/09/83 Ran 8 5/8" csg as follows: (Set @ 3788')  
10 jts 32# J-55 ST&C 391.5'  
28 jts 28# J-55 ST&C 1122.8'  
54 jts 24# J-55 ST&C 2164.0'  
3 jts 32# J-55 ST&C 107.5'  
Mix 1800 sx HOWCO lite w/1/4#/sx floceal & 15#/sx salt w/200 sx Cl "C" w/2% CaCl.

Subsurface Safety Valve: Manu. and Type

Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Ray TITLE Res. Engineer DATE December 21, 1983

(This space for Federal or State office use)

APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY

TITLE

DATE

ACCEPTED FOR RECORD

JAN 12 1984

RECEIVED

JAN 13 1984

O.C.D.  
HOBBS OFFICE