

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE
(Other instructions on reverse side)

Budget Bureau No. 1001
Expires August 31, 1985

LEASE DESIGNATION AND SERIAL NO.

NM-24166

IF INDIAN ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT" for such proposals.)

1. ☐ OIL WELL ☒ GAS WELL ☐ OTHER

2. NAME OF OPERATOR
POE PROPERTIES, INC.

3. ADDRESS OF OPERATOR
P. O. Box 9769, Fort Worth, Texas 76102

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surface
1650' FNL & 460' FEL of Section (Unit H)
(SE 1/4 NE 1/4)

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
3535' G.L.

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
SPRINKLE FEDERAL

9. WELL NO.
3

10. FIELD AND POOL, OR WILDCAT
Scharb - Wolfcamp

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 9-19S-35E

12. COUNTY OR PARISH
Lea

13. STATE
NM

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

16. NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF	☐	PULL OR ALTER CASING	☐	WATER SHUT-OFF	☐	REPAIRING WELL	☐
FRACURE TREAT	☐	MULTIPLE COMPLETE	☐	FRACURE TREATMENT	☐	ALTERING CASING	☐
SHOOT OR ACIDIZE	☐	ABANDON*	☐	SHOOTING OR ACIDIZING	☐	ABANDONMENT*	☐
REPAIR WELL	☐	CHANGE PLANS	☐	(Other)	☐	Casing Report	☒

(Other)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Spudded well on 6-10-84.

In a 17 1/2" hole, ran 350' of 13 3/8" (54.5#, K-55) casing and cemented with 400 sacks (Class "C" w/2% calcium chloride & 1/4# flocele/sack). Cement circulated.

In an 11" hole, ran 3526' of 8 5/8" (32#, K-55) casing and cemented with 1500 sacks (1200 sacks Halliburton lite w/15# salt and 1/4# flocele/sack and 300 sacks Class "C"). Cement circulated.

In a 7 7/8" hole, ran 10,800' of 5 1/2" (17#, N-80) casing and cemented with 600 sacks (50-50 Pozmix w/2% Gel, 6/10% Halad-22, 3# KCL/sack, and 1/2# flocele/sack).

I hereby certify that the foregoing is true and correct

SIGNED

James A. Knauf

(This space for Federal or State office use)

TITLE Agent

DATE 7-26-85

APPROVED FOR RECORD
CONDITIONS OF APPROVAL

TITLE

DATE

JUL 31 1985

*See Instructions on Reverse Side

RECEIVED

AUG - 8 1995

U.S. DEPARTMENT OF JUSTICE
FEDERAL BUREAU OF INVESTIGATION