

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in triplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy 1810'
T. Salt
B. Salt
T. Yates 3355'
T. 7 Rivers
T. Queen 4615'
T. Grayburg
T. San Andres 5107'
T. Glorieta
T. Paddock
T. Blinbry
T. Tubb
T. Drinkard
T. Abo
T. Wolfcamp
T. Penn.
T. Cisco (Bough C)

T. Canyon
T. Strawn
T. Atoka
T. Miss
T. Devonian
T. Silurian
T. Montoya
T. Simpson
T. McKee
T. Ellenburger
T. Gr. Wash
T. Granite
T. Delaware Sand 5987'
T. Bone Springs 7885'
T. 1st BS 9265'
T. 2nd BS 9827'
T. Scharb BS 10,045'

Northwestern New Mexico

T. Ojo Alamo
T. Kirtland-Fruitland
T. Pictured Cliffs
T. Cliff House
T. Menefee
T. Point Lookout
T. Mancos
T. Gallup
Base Greenhorn
T. Dakota
T. Morrison
T. Todilto
T. Entrada
T. Wingate
T. Chinle
T. Permian
T. Penn. "A"

T. Penn. "B"
T. Penn. "C"
T. Penn. "D"
T. Leadville
T. Madison
T. Elbert
T. McCracken
T. Ignacio Qtzite
T. Granite

OIL OR GAS SANDS OR ZONES

No. 1, from 9393' to 9405'
No. 2, from 9520' to 9577'
No. 3, from 9637' to 9725'
No. 4, from _____ to _____
No. 5, from _____ to _____
No. 6, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from _____ to _____ feet. None encountered
No. 2, from _____ to _____ feet.
No. 3, from _____ to _____ feet.
No. 4, from _____ to _____ feet.

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	286	286	Surface	9358	9787	429	Lime, Shale & Sand
286	402	116	Anhydrite & Red Beds	9787	9845	58	Shale & Dolo
402	1770	1368	Red Beds	9845	9955	110	Shale, Dolo, Sand
1770	2090	320	Red Bed & Anhy	9955	10007	52	Shale, Dolomite
2090	3353	1263	Anhy & Salt	10007	10293	286	Dolo & Shale
3353	3400	47	Anhy & Gyp				
3400	3442	42	Lime & Anhy				
3442	3522	80	Lime & Anhy				
3522	3629	107	Anhy & Lime				
3629	3840	211	Anhy, Gyp & Lime				
3840	3866	26	Anhy & Lime				
3866	6250	2384	Lime				
6250	7679	1429	Lime & Sand				
7679	8260	581	Lime, Sand & Shale				
8260	8917	657	Lime, Shale & Chert				
8917	9358	441	Lime & Shale				

RECEIVED

JUN 12 1984

O.C.D.
20848-10000