

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION  
P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-7

5a. Indicate Type of Lease  
State ☐ Fee ☒  
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE APPLICATION FOR PERMIT LIT (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Amoco Production Company	8. Farm or Lease Name Bryan
3. Address of Operator P. O. Box 68 Hobbs, NM 88240	9. Well No. 1
4. Location of Well UNIT LETTER <u>B</u> <u>660</u> FEET FROM THE <u>North</u> LINE AND <u>1980</u> FEET FROM THE <u>East</u> LINE, SECTION <u>13</u> TOWNSHIP <u>19-S</u> RANGE <u>35-E</u> N.M.P.M.	10. Field and Pool, or Wildcat Und. Wolfcamp
11. Elevation (Show whether DF, RT, GR, etc.) 3733.1' GL	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPS. ☐ PLUG AND ABANDONMENT ☐  
CASING TEST AND CEMENT JOBS ☒ OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled to a total depth of 11250'. On 3/22/84 ran 5-1/2", 17" and 15.5#, K-55 and N-80 casing. Casing set at 11258' with DV tool at 6985'. Circulated and pumped 70 bbl fresh water Pre-Flush. Cemented with 300 sx Class H Lite (containing 6% gel, 6#/sx salt, and 5#/sx gilsonite) and 525 sx Class H with .5% HALAD 22A. Displaced with 264 bbl water. Plug down 10:30 am 3/22/84. Dropped DV bomb and opened DV tool. Circulated 99 sxs cement. Pumped 70 bbl fresh water Pre-Flush, 275 sx class H Lite (with 6% gel, 6#/sx salt, and 5#/sx Gilsonite), 500 sx Class H with .5% HALAD 22A., 169 bbl fresh water. Plug down 4:15 pm 3/22/84. Rig released 3/22/84. Ran temperature survey and top of cement was found at 2725'. No further report until move in completion unit.

O+5 NMOCD, H J. R. Barnett, Hou Rm 21.156 1-F.J. Nash, Hou. Rm 4.206 1-GCC

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Amy C. Clark TITLE Ass't Admin. Analyst DATE 3/23/84

ORIGINAL SIGNED BY JERRY SEXTON  
DISTRICT I SUPERVISOR

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY:

MAR 30 1984

RECEIVED

MAR 28 1984

G.C.D.  
RECORDS OFFICE