STATE OF NEW MEXICO ENERGY AND MIMERALS DEPARTMENT

DISTRIBUTION		
SANTA FE		
FILE		
U.1.0.1,		
LAND OFFICE		
OPERATOR	1	1

OIL CONSERVATION DIVISION

Form	۲,	103	
Revis	e d	10-	1 - 7

DISTRIBUTION	P. O. BOX 2088	revised 10-1-7		
PILE	SANTA FE, NEW MEXICO 87501	Sc. Indicate Type of Leise		
U.S.O.S.		Stote Fee X		
DEGATOR		5. State Cli. 6 Gas Lease No.		
0.2.02	l e e e e e e e e e e e e e e e e e e e			
SUNDR'	Y NOTICES AND REPORTS ON WELLS			
(UD NOT USE THIS FORM FOR PROPOSALS TO PAILL OR TO DELETH OF PLUG BALL TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT =" (FORM C-101) FOR SUCH PROPOSALS.)		enoir.		
OIL X WELL .	OTHER-	7, Unit Agreement Name		
, Nanie of Operator		8. Farm or Lease Name		
Amoco Production Company		Bryan		
P. O. Box 68, Hobbs, NM 88240		1		
t. Location of Well	10, Field and Pool, or Wildcat			
UNIT LETTER B 66	Und. Wolfcamp			
THE East LINE, SECTION	ON 13 TOWNSHIP 19-S KANGE 35-E	HMPM.		
	15. Elevation (Show whether DF, RT, GR, etc.)	12. County		
	3733.1 GL	Lea		
Check	Appropriate Box To Indicate Nature of Notice,	Report or Other Data		
	•••	SUBSEQUENT REPORT OF:		
PERFORM REMEDIAL WORK	PLUG AND ABANDON REMEDIAL WORK	ALTERING CASING PLUG AND ABANDONMENT		
PULL OR ALTER CASING	CHANGE PLANS CASING TEST AND CEM			
THE OF RESEARCH	OTHER			
OTKER				
17. Duscribe Proposed or Completed Op- work) SEE RULE 1103.	perctions (Clearly state all pertinent details, and give pertinent	dates, including estimated date of starting any proposed		
•	s spud 2/11/84. Drilled to a total der	oth of 38'. Set 38' of 20"		
The subject well was spud 2/11/84. Drilled to a total depth of 38'. Set 38' of 20" con uctor pipe and cemented with 3 yds Redi-Mix. Moved in rigged up McVay Rig #8 and				
began continuous dr	illing operations on 2-17-84 with a 17-	-1/2" bit. Drilled to a total		
depth of 400° . On 2-18-84 ran 13-3/8", 54.5 #, J- 55 casing and set casing at 400° . Cemented				
with 450 sxs Class C cement with additives. Circulated out 200 sxs. WOC 18 hrs. Pressure tested casing 600 psi for 30 min. Held OK. Reduced bit to 11" and resumed drilling.				
tested casing 600 ps	si for 30 min. Held UK. Reduced bit i	to II and resumed drilling.		
0.5.40005	1 D : 5 O L Have to 21 150 1 5 1	Neels 110, 140, 1 000		
0+5-NMOCD, Hobbs	1-R. E. Ogden, Houston-21.150 1-F. J.	. Nash, Houston-4.206 1-GCC		
		·		
		•		
•				
18.1 hereby curtify that the information	n chove is true and complete to the best of my knowledge and b	CIPEL.		
Then (1)	Asst. Admin. Ana	lyst 2-23-84		
BIGHED WAY	YHTE 11350. Maiiriii. Mia	DATE L LU-UT		
ORIGINAL SIG	GNED BY JERRY SEXTON			
	CT I SUPERVISOR	E ER 27 198 4		

HOED SA 1984