30-025-28656

NO. OF COPIES RECEIVED										
DISTRIBUTION		NEW	MEXICO (OIL CONSER	VATION COA	MISSION		Form C-101		
SANTA FE								Revised 1-1-	65	
FILE									e Type of Lease	
U.S.G.S.								STATE		
DERATOR								. 3. State OII	& Gas Lease No.	
OPERATOR								mm.	mmmm	
APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK										
1a. Type of Work								7. Unit Agr	eement Name	
DRILL XX]		DEEPEN			PLUG B	ACK 🗆			
b. Type of Well	f Weil							8. Farm or Lease Name		
OIL XX GAS SINGLE XX MULTIPLE ZONE ZONE								Scharb "9"		
2. Name of Operator								9. Well No.		
Southland Royalty Company 3. Address of Operator								4	and Dool on Wildow	
								10. Field and Pool, or Wildcat		
21 Desta Drive, Midland, Texas 79705 4. Location of Well UNIT LETTER C LOCATED 2086 FEET FROM THE West LINE								Scharb (Bone Springs)		
UNIT LETT	ER	LOCA	TED	<u>00 </u>	ET FROM THE	West	LINE			
AND 766 FEET FROM	тне N	lorth Line	OF SEC.	9 тw	r. 19S	RGE. 3	5E HMPM			
	7717	HIIIII				77777	THIN	12. County	1111111	
								Lea		
411111111111111111111111111111111111111	77777			1111111	, Proposed De		A. Formation	777777	20, Rotary or C.T.	
				//////						
21. Elevations (Show whether DF	RT, etc.)	21A, Kind	S Status P		9900 ¹ B. Drilling Cor		one Spr		Rotary z. Date Work will start	
3846.6' GR	, ,			-,-				4-9-84		
23.			· · · · · · · · · · · · · · · · · · ·					14-9-05	Ł	
		PI	ROPOSED	CASING AND	CEMENT PRO	GRAM				
SIZE OF HOLE	SIZE	SIZE OF CASING		PER FOOT	SETTING DEPTH SACKS O		SACKS OF	CEMENT	EST. TOP	
17 1/2"		13 3/8"			1		400 s	Χ	Circulate	
12 1/4"		5/8"	24 & 2		4000'		2000 sx.		Circulate	
7 7/8"	5	1/2"	15.5 &	17#	9900'		900 sx.		T0 © @ 7500' +	
Drill 17 1/2" hole to 410'. Set 13 3/8" csg @ 410'. Cmt w/400 sx cmt & circ. Drl 12 1/4" hole to 4000'. Set 8 5/8" csg @ 4000'. Cmt w/2000 sx. cmt & circ. Drl 7 7/8" hole to 9900'. Set 5 1/2" csg @ 9900'. Cmt w/sufficient volume to cover all prospective zones. Est top of cmt @ 7500'. Perf and stimulate Bone Springs for production. MUD PROGRAM: 0-410' spud mud, 410-4000' Salt wtr; 4000-9000' Cut brine wtr; 9000-9900' Salt wtr gel & Drispac. MW 9.4-9.7, VIS 40, 10-15 cc. BHP @ TD anticipated to be 4000 psi. No abnormal pressures expected. BOP PROGRAM: BOP to be tested after each new installation and after setting 8 5/8" csg by Yellow Jacket, Inc. Test BOP @ 6500 & 9500'. APPROVAL VALID FOR 180 DAYS PERMIT EXPIRES 912.1/84										
	ROPO S ED	PROGRAM: IF P	ROPOSAL IS	TO DEEPEN OR		UNLE	iss drill	ING Ú ŃD	ERWAY	
TIVE ZONE, GIVE SLOWOUT PREVENT	ER PROGRA	AM, IF ANY.								
I hereby certify that the information	on above	is true and comp	lete to the	best of my kno	wledge and be	Hef.				
Signed Lunch Fol	s.to		Title	Operatio	ns Engine	er	<u> </u>	Date	3-26-84	
(This space for	e W. S	eay Effector	TITLE_					oatMAR	2 7 19 84	

MAR OCH TON

4"
