



2 2" BELL, 1500 HALF-TYPE HOSE (8)

3 3" BELL, 1500 VALVE

4 BELL, 1500 MULTIPLE SPool

5 2" BELL, 1500 X 2" BELL, 1500 STEEL TEE

6 2" BELL, 1500 VALVE

7 2" BELL PRESSURE GAUGE

8 3" BELL, 1500 X 2" BELL, 1500 STEEL CROSS

9 2" BELL, 1500 AND, CHOICE

10 2" BELL, 1500 AND, CHOICE OR 2" BELL, 1500 BELL VALVE OR 3" BELL, 1500 STEEL TEE

11 ADAPTER, 2" BELL, 1500 X 10,000 LB FLANGE MATING (12) INLET

12 10,000 LB WP MEMOTE CHOICE

13 HYDRAULIC CHOICE, 2500 LB WP OR BETTER

14 3" BELL, 1500 CHECK VALVE

NOTES

1. 6000 PSI OR BETTER CLASS WITH 1000 PSI MAY BE SUBSTITUTED FOR FLANGES
2. ONE ADJUSTABLE CHOICE MAY BE REPLACED WITH A POSITIVE CHOICE
3. VALVES MAY BE EITHER HAND OR POWER OPERATED BUT, IF POWER OPERATED, THE VALVE IS FLANGED TO THE TOP AND MUST BE CAPABLE OF BEING OPERATED AND CLOSED MANUALLY OR CLOSE OR POWER FAILURE AND BE CAPABLE OF BEING OPERATED MANUALLY

5000 PSI WORKING PRESSURE BLOWOUT PREVENTER 1100K-1 SERIES 1500 FLANGES ON BELL

RECEIVED
APR 19 1984
O.C.O.
HOBB'S OFFICE