

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

5a. Indicate Type of Lease	
State ☒	Fee ☐
5. State Oil & Gas Lease No.	
LG-1784	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐		7. Unit Agreement Name
2. Name of Operator Harvey E. Yates Company		8. Farm or Lease Name Amoco East 2 State
3. Address of Operator P. O. Box 1933, Roswell, New Mexico 88201		9. Well No. 2
4. Location of Well UNIT LETTER K 1980 FEET FROM THE South LINE AND 1980 FEET FROM THE West LINE, SECTION 2 TOWNSHIP 18S RANGE 32E N.M.P.M.		10. Field and Pool, or Wildcat Und. Bone Springs
15. Elevation (Show whether BF, RT, GR, etc.) 3870.2 GL		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☒	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☒	OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 103.

8/05/84 RIH w/5 1/2" casing as follows:

18 jts	N-80	17#	LT&C	705.01'
1 jt	N-80	17#	LT&C	31.83'
45 jts	J-55	17#	LT&C	1940.72'
119 jts	J-55	15.5#	LT&C	4804.68'
22 jts	J-55	17#	LT&C	959.50'
22 jts	N-80	17#	LT&C	867.90'

TOTAL 227 jts 9309.64'

Cmt w/500 sxs class H w/18% salt & .2% D65 mixed @ 16.7#/gal.

8/09/84 Perf Bone Springs @ 8764', 68', 86', 8800', 20', 28', 48', 54', 62', 8922', 30' (1 SPF). Acidize w/2500 gal 7 1/2% SRA & 22 ball sealers.

8/11/84 Frac lower Bone Springs perfs from 8764' to 8930' w/87000 gal EZ Frac 50 w/100,000# 20/40 sd.

8/14/84 Perf Bone Springs @ 8568' to 8737'.

8/15/84 Acidize w/2500 gal 7 1/2% SRA w/22 Ball sealers.

8/17/84 Set RBP @ 8670', set pkr @ 8476'.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Ray T. [Signature] TITLE Reservoir Engineer DATE 8/20/84

APPROVED BY Eddie W. Seay TITLE Oil & Gas Inspector DATE AUG 22 1984

RECEIVED

AUG 21 1984

O.C.D.
HOBBS OFFICE