

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE\*  
(Other instructions on reverse side)

Form approved.  
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT" for such proposals.)

5. LEASE DESIGNATION AND SERIAL NO.

NM 57285

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Stivason Federal

9. WELL NO.

#1

10. FIELD AND POOL, OR WILDCAT

Pearl Queen

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

33-19-34

12. COUNTY OR PARISH 13. STATE

Lea

NM

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

3. MorOilCo, Inc.  
ADDRESS OF OPERATOR

4. P.O. Drawer 1 Artesia, NM 88210  
LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

330 FNL 330 FEL

14. PERMIT NO. Unit A

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Spud; 8-5/8" casing report

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spud 12 1/4" hole at 8:00 p.m., May 31, 1984. Drilled to 1535'. Ran 36 jts. of 8 5/8" 24#, J-55; Texas pattern notched guide shoe and set at 1533'. Cement with 400 sx. Pacsetter-lite C 2% CaCl and 200 sx. Cl "C" 2% CaCl. Circulate 160 sx. to pit. Plug down at 11:00 p.m. Wait 18 hrs on cement. Test casing to 1000#'s for 30 min. O.K.

18. I hereby certify that the foregoing is true and correct

SIGNED Frank S. Mays

TITLE Operator

DATE June 3, 1984

(This space for Federal or State office use)

APPROVED BY LWF

TITLE

DATE

CONDITIONS OF APPROVAL JUN 7 1984

Carlsbad NEW MEXICO

\*See Instructions on Reverse Side

RECEIVED

JUN 8 1984

C.L.D.  
HOBBS OFFICE