

INSTRUCTIONS

This form is to be filled with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled, deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filled in quintuplicate except state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy 1809'	T. Canyon	T. Ojo Alamo	T. Penn. "B"
T. Salt	T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt	T. Atoka	T. Pictured Cliffs	T. Penn. "D"
T. Yates 3343'	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers	T. Devonian	T. Menefee	T. Madison
T. Queen 4600'	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg	T. Montoya	T. Mancos	T. McCracken
T. San Andres 5084'	T. Simpson	T. Gallup	T. Ignacio Qtzite
T. Glorieta	T. McKee	Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger	T. Dakota	T.
T. Blinbry	T. Gr. Wash	T. Morrison	T.
T. Tubb	T. Granite	T. Todilto	T.
T. Drinkard	T. Delaware Sand 5973'	T. Entrada	T.
T. Abo	T. Bone Springs 7818'	T. Wingate	T.
T. Wolfcamp	T. Bone Springs 9256'	T. Chinle	T.
T. Penn.	T. Bone Springs 9833'	T. Permian	T.
T. Cisco (Bough C)	T. Scharb 10009'	T. Penn. "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from 9540' to 9572'	No. 4, from 9622' to 9709'
No. 2, from 9392' to 9402'	No. 5, from 9834' to 9844'
No. 3, from 9540' to 9572'	No. 6, from 10036' to 10087'

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from	to	feet	None Encountered
No. 2, from	to	feet	
No. 3, from	to	feet	
No. 4, from	to	feet	

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	417	417	Surface	7945	8339	394	Lime, Dolo
417	1190	773	Red Bed	8339	8381	42	Lime, Shale
1190	1987	797	Red Bed & Anhy.	8381	8607	226	Lime
1987	2406	419	Anhy.	8607	9317	710	Lime & Chert
2406	2806	400	Red Bed & Anhy.	9317	9414	97	Lime, Shale, Sd & Chert
2806	4653	1847	Anhy.	9414	9915	501	Lime, Shale
4653	4849	196	Anhy. & Shale	9915	9956	41	Dolo, Lime
4849	4995	146	Anhy. & Lime	9956	10025	69	Lime, Dolo
4995	6042	1047	Lime	10025	10250	225	Lime, Shale, Dolo
6042	6158	116	Anhy. & Lime				
6158	7248	1090	Lime & Sand				
7248	7575	327	Lime & Shale, Dolo				
7575	7945	370	Lime, Dolo & Sd.				

DEC 31 1984

OFFICE