

NEW MEXICO 88240

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

- 1. oil well [X] gas well [ ] other [ ]
2. NAME OF OPERATOR Harvey E. Yates Company
3. ADDRESS OF OPERATOR P. O. Box 1933, Roswell, NM 88201
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 1650' PNL & 1980' FWL AT TOP PROD. INTERVAL: AT TOTAL DEPTH: Same
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE REPORT, OR OTHER DATA

5. LEASE NM40453
6. IF INDIAN, ALLOTTEL OR TRIBE NAME
7. UNIT AGREEMENT NAME Young Deep Unit
8. FARM OR LEASE NAME
9. WELL NO. 11
10. FIELD OR WILDCAT NAME North Young Bone Springs
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 9, T-18S, R-32E
12. COUNTY OR PARISH, 13. STATE Lea NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD) 3818.9 GL

REQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF, FRACTURE TREAT, SHOOT OR ACIDIZE, REPAIR WELL, PULL OR ALTER CASING, MULTIPLE COMPLETE, CHANGE ZONES, ABANDON\* (other) Spud & Run Casing
SUBSEQUENT REPORT OF:

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

8/6/84 Spud @ 6:30 PM 8/5/84.
8/7/84 Ran 15 jts 54.5# 13 3/8" casing. Set @ 602'. Cmt w/250 sxs HLW, 2% CaCl 1/4# floreal, tail in w/200 sxs class "C" w/2% CaCl. Test to 1000# - OK.
8/10/84 RIH w/8 5/8" casing as follows:

Table with 5 columns: jts, #, J-55, ST&C, and depth. Rows: 10 jts 32# J-55 ST&C 412.04', 54 jts 24# J-55 ST&C 2272.96', 64 jts TOTAL 2685.00'

Set @ 2680', cmt w/700 sxs Halliburton Lite w/18% salt w/1/4# floreal. Tail in w/200 sxs class "C" w/2% CaCl. Test to 1000# - Held OK.

Subsurface Safety Valve: Manu. and Type Set @ Ft.

18. I hereby certify that the foregoing is true and correct
SIGNED [Signature] TITLE Res. Engineer DATE August 20, 1984

ACCEPTED FOR RECORD (This space for Federal or State office use)

APPROVED BY [Signature] TITLE DATE
CONDITIONS OF APPROVAL, IF ANY AUG 22 1984

RECEIVED

AUG 24 1984

C.C.D.  
HOSES OFFICE