

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other
well well

2. NAME OF OPERATOR

C. W. Stumhoffer

3. ADDRESS OF OPERATOR Suite 1007 Ridglea Bank Bldg.
Fort Worth, Texas 76116

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 660' FNL and 330' FEL Section 26

AT TOP PROD. INTERVAL: Same

AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) Completion ☐

SUBSEQUENT REPORT OF:

☐

☒

☒

☐

☐

☐

☐

☐

☐

5. LEASE

NM 57285

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

-

7. UNIT AGREEMENT NAME

-

8. FARM OR LEASE NAME

Stivason Federal

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Pearl Queen

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

26, T19S, R34E, NMPM

12. COUNTY OR PARISH 13. STATE

Lea

New Mexico

14. API NO.

30-025-28796

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3773.5' KDB

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Completion operations were commenced on 10/9/84. Welex ran GR-collar correlation log and perforated Queen Sand from 4922'-30' KDB w/ 18-0.375" holes w/ casing gun on 10/10/84. PBTD 5136' KDB.

Acidized Queen Sand perforations on 10/10/84 with 500 gallons 15% NE Acid and swab tested well.

Fracture treated Queen sand perforations on 10/11/84 with 20000 gallons gelled fresh water, 11000 # 20/40 sand, and 8500 # 10/20 sand.

Well placed on pump on 10/13/84.

Subsurface Safety Valve: Manu. and Type N/A Set @ N/A Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED C. W. Stumhoffer TITLE Operator DATE January 9, 1985
C. W. Stumhoffer

(This space for Federal or State office use)

APPROVED BY ACCEPTED FOR RECORD TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY None

JAN 17 1985

NEW MEXICO

RECEIVED

JAN 21 1985

RECEIVED
FEDERAL BUREAU OF INVESTIGATION
U.S. DEPARTMENT OF JUSTICE