

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐  
well well

2. NAME OF OPERATOR  
C. W. Stumhoffer

3. ADDRESS OF OPERATOR Suite 1007 Ridglea Bank Bldg.  
Fort Worth, Texas 76116

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 660' FNL and 330' FEL Section 26  
AT TOP PROD. INTERVAL: Same  
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	<input type="checkbox"/>		<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>		<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>		<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>		<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>		<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>		<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>		<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>		<input type="checkbox"/>
(other) Running Production Casing			

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

C. W. Stumhoffer's Stivason Federal No. 1 well was drilled to a total depth of 5175' KDB, which depth was reached on 9/09/84.

After running Welex Guard-Forxo Compensated Density-Dual Spaced Neutron open hole logs, 5½" OD, 17#, N-80, LT&C production casing was run and set at a depth of 5175' KDB. Production casing was cemented with 360 sacks Class C 50/50 pozmix w/0.5 of 1% Halad 9, 2% gel. Plug down @3:45 PM 9/10/84. Plug pressured to 1800 psig, held, and released. Estimated top of cement base of salt @ 3266' KDB.

Subsurface Safety Valve: Manu. and Type N/A Set @ N/A Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED C. W. Stumhoffer TITLE Operator DATE January 9, 1985  
C. W. Stumhoffer

(This space for Federal or State office use)

APPROVED BY ACCEPTED FOR RECORD TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

JAN 17 1985

\*See Instructions on Reverse Side

NEW MEXICO

5. LEASE  
NM 57285

6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
-

7. UNIT AGREEMENT NAME  
-

8. FARM OR LEASE NAME  
Stivason Federal

9. WELL NO.  
1

10. FIELD OR WILDCAT NAME  
Pearl Queen

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
26, T19S, R34E, NMPM

12. COUNTY OR PARISH  
Lea

13. STATE  
New Mexico

14. API NO.  
30-025-28796

15. ELEVATIONS (SHOW DF, KDR AND WD)  
3773.5' KDB

(NOTE: Report results of multiple completion or zone change on Form 9-330.)