

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-79

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. LG 2363	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Re-Entry		7. Unit Agreement Name
2. Name of Operator Yates Petroleum Corporation		8. Farm or Lease Name ARCO State
3. Address of Operator 105 South 4th St., Artesia, NM 88210		9. Well No. 1
4. Location of Well UNIT LETTER N 660 FEET FROM THE South LINE AND 2120 FEET FROM THE West LINE, SECTION 16 TOWNSHIP 18S RANGE 32E N.M.P.M.		10. Field and Pool, or Wildcat South Maljamar Grayburg
15. Elevation (Show whether DF, RT, GR, etc.) 3773.5' GR		12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> OTHER <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/> REMEDIAL WORK <input type="checkbox"/> COMMENCE DRILLING OPNS. <input type="checkbox"/> CASING TEST AND CEMENT JOBS <input type="checkbox"/> OTHER Squeeze, perforate, treat <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

3-25-88. Set retainer at 4313'. Squeeze perforations 4374-82' w/100 sx Class "C" Neat to 2700 psi. Reverse out 20 sx cement. TIH with 4" casing gun and perforated 3830-48' w/19 .42" holes (1 SPF). Acidized perforations 3830-48' w/2500 gals 7½% NEFE acid and ball sealers.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Jerry Sexton TITLE Production Supervisor DATE 3-30-88

APPROVED BY JERRY SEXTON

DISTRICT 1 SUPERVISOR

CONDITIONS OF APPROVAL, IF ANY: