Form 9-331 Dec. 1973

HODES, NEW MEXICO 88240

Form Approved

UNITED STATES		
DEPARTMENT OF THE INTERIO)	R
GEOLOGICAL SURVEY	į	

HAUTED CTATEO	Budget Bureau No. 42-R1424
UNITED STATES	5. LEASE
DEPARTMENT OF THE INTERIOR	NM-40456
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)	
reservoir, use Form 9-331-C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas uther	Sprinkle 'B' Fed.
	9. WELL NO.
2. NAME OF OPERATOR	1
Metex Pipe & Supply	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Und. Queen
2407 Sierra Vista Artesia, N. M. 88210	11. SEC., T., R., M., OR BLK. AND SURVEY OF
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)	AREA 32
AT SURFACE: 2310' FNL & 1980' FWL	<u>S-1, T-18S, R-3≠</u> E
AT TOP PROD. INTERVAL:	12. COUNTY OR PARISH 13. STATE
AT TOTAL DEPTH:	Lea NM
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	14. API NO.
REPORT, OR OTHER DATA	
	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	3911.5' GL
TEST WATER SHUT-OFF	
FRACTURE TREAT	
SHOOT OR ACIDIZE	
PULL OR ALTER CASING	(NOTE: Report results of multiple completion or zone
MULTIPLE COMPLETE	change on Form 9-330.)
CHANGE ZONES 🗍 🦷	
ABANDON* ☐ 😾	
(other)	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statincluding estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertiner	e all pertinent details, and give pertinent dates, irectionally drilled, give subsurface locations and it to this work.)*
A cast iron bridge plug was set at 3998'. The and pulled. Class "C" cement was pumped as fol	5½" casing was cut off at 3321'
50' on top of the C.I.B.P. from 3998' t	lows:
100' of cement was numbed between 20711	0 3940'.
100' of cement was pumped between 3271'	and 3371'.
35 Sacks of cement was pumped at 450' a	nd was tagged at 380'.
35 sacks of cement was pumped at surface	e.
All cement plugs had 9 1b mud in betwee	
Dry hole marker will be set and location restowhen ready for final inspection.	red, BLM will be notified
Subsurface Safety Valve: Manu. and Type	_
· · · · · · · · · · · · · · · · · · ·	Set @

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 2310' FNL & 1980' FWL AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE П REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES \prod ABANDON* (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertiner A cast iron bridge plug was set at 3998'. The and pulled. Class "C" cement was pumped as fol 50' on top of the C.I.B.P. from 3998' t 100' of cement was pumped between 3271' 35 Sacks of cement was pumped at 450' a 35 sacks of cement was pumped at surfac All cement plugs had 9 1b mud in betwee Dry hole marker will be set and location resto when ready for final inspection. Subsurface Safety Valve: Manu. and Type ____ 18. I hereby certify that the foregoing is true and correct SIGNED TITLE Operator DATE November 15, 1986 Orig. Sgd. Linda S. C. Kunder (This space for Federal or State office use) Acting Area Mignoger APPROVED BY TITLE _ DATE CONDITIONS OF APPROVAL, IF ANY:

May 1 100 s