

N. M. OIL CONS. COMMISSION  
P. O. BOX 1900  
HOBBS, NEW MEXICO 88240

Form Approved.  
Budget Bureau No. 42-R1424

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐  
well well  
2. NAME OF OPERATOR  
Harvey E. Yates Company  
3. ADDRESS OF OPERATOR  
P. O. Box 1933, Roswell, New Mexico 88201  
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 585' FNL & 2055' FEL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH: Same  
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input checked="" type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>
(other)	

5. LEASE  
NM-9018  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
7. UNIT AGREEMENT NAME  
Young Deep Unit  
8. FARM OR LEASE NAME  
9. WELL NO.  
14  
10. FIELD OR WILDCAT NAME  
North Young Bone Springs  
11. SEC., T., R., M. OR BLK. AND SURVEY OR AREA  
Sec. 9, T-18S, R-32E  
12. COUNTY OR PARISH 13. STATE  
Lea NM  
14. API NO.  
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3836' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

12/12/84 Perf 9092' to 9108' (2 spf). Spot 250 gal SRA 15%.  
12/13/84 Set CIBP @ 9075' w/35 sxs cmt on top. PBTD 9040'.  
12/15/84 Perf 8374' to 8380', 8390' to 8400' & 8410' to 8425' (2 spf).  
12/18/84 GIH w/2 3/8" tbq & pkr to 8426'. Spot 250 gal 20% SRA.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED *A. P. Operations* TITLE V. P. Operations DATE 12/18/84  
ACCEPTED FOR RECORD

(This space for Federal or State office use)

APPROVED BY *[Signature]* TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL DEC 21 1984

*Carlsbad,* NEW MEXICO \*See Instructions on Reverse Side