

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
NEW MEXICO 83240

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

NM-9018

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Young Deep Unit

8. FARM OR LEASE NAME

9. WELL NO.

15

10. FIELD AND POOL, OR WILDCAT

North Young Bone Springs

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 9, T-18S, R-32E

12. COUNTY OR PARISH 13. STATE

Lea

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Harvey E. Yates Co.

3. ADDRESS OF OPERATOR

P.O. Box 1933, Roswell, NM 88201

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1650' FNL & 1980' FEL

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3830' GL

14. PERMIT NO.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☒

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 6-24-85: Squeeze perms @ 8525-8548' w/150 sxs class "H" w/Flac. Circ. 10 sxs to pit (140 sxs under ret).
6-29-85: Drld out to 9034' (PBSD).
7- 1-85: Perf upper Bone Springs @ 8432-8444' (2 spf, 24 holes). Acidize w/1000 gal acid & 20 ball sealers.
7- 5-85: Run tbg, SN to 9000' & tbg anchor to 8330'. Run pump & rods. Hang well on production.

18. I hereby certify that the foregoing is true and correct

SIGNED

Stephen R. Lake

TITLE Asst. Engineer

DATE 7-22-85

(This space for Federal or State office use)

APPROVED BY ACCEPTED FOR RECORD TITLE

CONDITIONS OF APPROVAL, IF ANY:

DATE

JUL 28 1985

*See Instructions on Reverse Side