

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐
well well other

2. NAME OF OPERATOR
Harvey E. Yates Company

3. ADDRESS OF OPERATOR

P. O. Box 1933, Roswell, New Mexico 88201

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1980' FNL & 660' FWL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☐
☒
☐
☐
☐
☐
☐
☐

5. LEASE
LC-065581

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME
Young Deep Unit

8. FARM OR LEASE NAME

9. WELL NO.
16

10. FIELD OR WILDCAT NAME
North Young Bone Springs

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 9, T-18S, R-32E

12. COUNTY OR PARISH: 13. STATE

Lea NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3813.3 GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1/16/85 Tag DV tool @ 3942'. Start drilling DV tool and cmt.
1/18/85 Finish drilling DV tool and cmt to 9335'.
2/02/85 Perf 9299' to 9306' & 9318' to 9326' (2 JSPF).
2/05/85 Spot 200 gal 20% SRA @ 9299 to 9326'.
2/06/85 Set retainer @ 9290' & sqz perfs 9299' to 9326' w/100 sxs cmt. Sqz to 4000#
w/45 sxs cmt in formation.
2/07/85 Perf 9259' to 9263' (2 spf).
2/09/85 Set CIBP @ 9230', dump 35' cmt on top, new PBD @ 9195'. Perf @ 8484' to 8496'
(2 spf).
2/10/85 Spot 200 gal 15% SRA @ 8500'.
2/12/85 Perf @ 8425' to 8435' (2 spf).
2/13/85 Spot 200 gal on perf @ 8425' to 8435'.
2/15/85 Perf 8367' to 8380'.
Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED A. M. Yates TITLE Dirg. Superinten. DATE 2/26/85

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____
CONDITIONS OF APPROVAL, IF ANY: _____

DATE _____

MAR 1 1985