

UNITED STATES
HOBBS, NEW MEXICO
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR	8. FARM OR LEASE NAME
3. ADDRESS OF OPERATOR	9. WELL NO.
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface	10. FIELD AND POOL, OR WILDCAT
330 FSL 1650 FEL	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Unit 0	12. COUNTY OR PARISH
14. PERMIT NO.	13. STATE
15. ELEVATIONS (Show whether DF, RT, GR, etc.)	
3689.5' GR	

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF	PULL OR ALTER CASING
FRACTURE TREAT	MULTIPLE COMPLETE
SHOOT OR ACIDIZE	ABANDON*
REPAIR WELL	CHANGE PLANS
(Other)	

SUBSEQUENT REPORT OF:

WATER SHUT-OFF	REPAIRING WELL
FRACTURE TREATMENT	ALTERING CASING
SHOOTING OR ACIDIZING	ABANDONMENT*
(Other) Spud: 8-5/8" casing report	X

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

Spud 12-1/4" hole @7:00 p.m., Dec. 20, 1984. Drill to 1575'. Ran 38 joints 24#, J-55; Texas pattern notched guide shoe & set @ 1573'. Cemented with 400 sx. Howco Lite & tailed in with 150 sx. Class "C", 2% CaCl, 1/4# floseal. Circulate 50 sx. to pit. Plug down @2:00 a.m., Dec. 23, 1984. Wait 18 hours on cement. Test casing to 1,000#'s for 30 min. O.K.

18. I hereby certify that the foregoing is true and correct

SIGNED Frank J. Muegen TITLE Operator DATE 12/27/84

(This space for Federal or State office use)

APPROVED BY 92/6 TITLE DATE

CONDITIONS OF APPROVAL

*See Instructions on Reverse Side