

WRS COMPLETION REPORT

COMPLETIONS SEC 20 TWP 19S RGE 35E
PI# 30-T-0015 03/25/88 30-025-29145-0001 PAGE 1

NMEX LEA * 520FNL 2120FWL SEC NE NW
STATE COUNTY FOOTAGE SPOT
MANZANO OIL D X DO
OPERATOR WELL CLASS INIT FIN
1 RICHARDSON
WELL NO LEASE NAME
3824GR SCHARB
OPER ELEV FIELD POOL AREA
API 30-025-29145-0001

12/14/1987 01/05/1988 WO-UNIT OIL-WO
SPUD DATE COMP. DATE TYPE TOOL STATUS
9900 BONE SPG NOT RPTD
PROJ. DEPTH PROJ. FORM CONTRACTOR
DTD 10170 PB 9912 OTD 10170 FM/TD BONE SPG
DRILLERS T.D. LOG T.D. PLUG BACK TD OLD T.D. FORM T.D.

LOCATION DESCRIPTION

11 MI S BUCKEYE, NM

CASING/LINER DATA

CSG 4 1/2 @ 9993 W/ 275 SACKS

INITIAL POTENTIAL

IPP 5BOPD 40BW 24HRS
BONE SPG PERF W/ 28/IT 9671- 9721 GROSS
PERF 9671, 9674, 9675, 9678, 9681, 9682, 9686, 9687
PERF 9688, 9689, 9690, 9691, 9692, 9693, 9694, 9695
PERF 9696, 9698, 9699, 9700, 9701, 9702, 9703, 9708
PERF 9711, 9712, 9713, 9721
ACID 9671- 9721 4000GALS
15% NEFE
SWFR 9671- 9721 1580BBLs 135000LBS SAND

ADDITV GELA

20/40

GTY NR; GOR TSTM

DRILLING PROGRESS DETAILS

MANZANO OIL
BOX 2107
ROSWELL, NM 88201
505-623-1996
OWWO: OLD INFO: FORMELRY GULF OIL 1 PEOPLES
SECURITY "D". ELEV 3824 GR. SPUD 2/26/85. 11 3/4

CONTINUED IC# 300257042587

COMPLETIONS SEC 20 TWP 19S RGE 35E
PI# 30-T-0015 03/25/88 30-025-29145-0001 PAGE 2

MANZANO OIL
1

RICHARDSON

D X DO

DRILLING PROGRESS DETAILS

@ 450 W/400 SX, 8 5/8 @ 4192 W 300 SX. LOG TOPS:
BONE SPRING 8055, 1ST BONE SPRING SD 9608, 2ND
BONE SPRING SD 10054. OTD 10170. COMP 3/28/85.
D&A.

12/11 LOC/1987/

03/23 DOC TO 10000

RAN 4 1/2 CSG

PB TO 9912

03/23 10170 TD, PB 9912

COMP 1/5/88, IPP 5 BO, 40 BWPD, GOR
(TSTM), GTY (NR)

PROD ZONE - BONE SPRING 9671-9721

COUNTY	LEA	FIELD	Scharb	STATE	NM
OPR	CHEVRON USA	API	30-025-29145		
NO	1	LEASE	Peoples Security "D"	MAP	
Sec 2C, T19S, R35E		520 FTL, 2120 FWL of Sec		9-4-26 NM	
11 mi S/Buckeye		SPD	2-26-85	MP	3-28-85
CSC	WELL CLASS: INIT D FIN D USE CODE				
11 3/4-450-400 sx	FORMATION	DATUM	FORMATION	DATUM	
8 5/8-419-300 sx					
	TD 10,170 (ESPG)		PRC		

DRY & ABANDONED

WATER EXECUTED BY #57 OPERATOR 5824 GR, 5841 KE 945 D

W.R. 2-25-85
 TD 10,150 RT (Bone Spring)
 9-28-85 AMEND OPERATOR: Formerly Gulf Oil
 3-1-85 Drlg 2110 salt & anhy
 1-28-85 Drlg 4200
 3-11-85 Drlg 5841 1m & sh
 mw 8.9, vis 29
 1-10-85 Drlg 9313 1m & sh
 mw 8.7, vis 29
 3-21-85 TD 10,170; Rng DST
 Drlg break 9690-9740
 DST (Bone Spring) 9550-10,025, op 1 hr 5 mins,
 rec 30 FT WTR (Sample chamber rec 100 CG WTR),
 5 min IFP 86-129, 1 hr FSIP 236, 1 hr CFP 129-
 129, 2 hr FSIP 258, HP 4454-4454, RRI 728 log
 No Cores

9-4-26 NM

LEA
CHEVRON USA

Scharb
1 Peoples Security "D"
Sec 20, TRES, R35E

NM
Page 2

4-1-85

TD 10,170; D&A
DST (STRD) (Bone Spring) 9790-9850, op 1 hr 5
mins, rec 100 FT MUD (Sample chamber rec 125
CC WTR), 5 min IEP 77-92, 1 hr ESIP 262, 1 hr
FFP 78-78, 2 hr ESIP 276, HP 4461-4453, BFE
136 deg @ 9850

9-23-85

TD 10,170; Dry & Abandoned
LOG TOPS: Rustler 1803, Yates 3470, Saxon
Rivers 4004, Queen 4456, San Andres 5392,
Belmore Sand 6101, Bone Spring 8050, 1st Bone
Spring Sand 2408, 2nd Bone Spring Sand 4434
FOOT WLS: PCL, G, ADT, G, PRAL
Rig released 5-10-85 9-4-86 NM
COMPLETION ISSUED TC 50-078-70087-85

9-28-85