

OIL CONSERVATION DIVISION

P.O. Box 2088

Santa Fe, New Mexico 87504-2088

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

WELL API NO.	30-025-29163
5. Indicate Type of Lease	STATE ☒ FEE ☐
6. State Oil & Gas Lease No.	
7. Lease Name or Unit Agreement Name	Bridges State #196
8. Well No.	196
9. Pool name or Wildcat	Vacuum Grayburg (SanAndres)

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL ☒ GAS WELL ☐ OTHER ☐	
2. Name of Operator Mobil Producing TX & NM Inc.* *Mobil Exploration & Producing US Inc. as agent for MPTM	
3. Address of Operator P.O. Box 633, Midland, TX 79702	
4. Well Location Unit Letter C : 1188 Feet From The North Line and 1357 Feet From The West Line Section 24 Township 17-S Range 34-E NMPM Lea County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) GL 4020	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK ☐	REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐	ALTERING CASING ☐
PULL OR ALTER CASING ☐	COMMENCE DRILLING OPNS. ☐
OTHER: ☐	PLUG AND ABANDONMENT ☐
	CASING TEST AND CEMENT JOB ☐
	OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- MIRU PU. DIG PIT. FLOW WELL BACK TO PIT. ND WH. NU BOP.
- RIH W/ WS TO CIBP @ 4295'. LOAD HOLE W/ 10 PPG GELLED BRINE. SPOT 25 SX CLASS C NEAT CMT CAP ON TOP OF CIBP.
- PUH TO 3000'. SPOT 20 SX CLASS C NEAT CMT PLUG ACROSS YATES TOP @ 2925' FROM 3000-2850'.
- PUH TO 1835'. SPOT 30 SX CLASS C NEAT CMT PLUG ACROSS CSG SHOE @ 1710' & SALT TOP FROM 1835-1635'.
- PUH TO 30'. SPOT 10 SX CLASS C NEAT CMT PLUG FROM 30'-SURFACE. POOH W/ WS.
- ND BOP. RD PU. DIG OUT CELLAR AND CUT CSG 3' BELOW SURFACE. WELD STEEL PLATE ON CSG STUB. ERECT P&A MARKER WITH WELL NAME AND PLUGGED DATE. FILL CELLAR AND CLEAN SURFACE LOCATION.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Kaye Pollock TITLE Regulatory Technician DATE 08-16-93
TYPE OR PRINT NAME Kaye Pollock TELEPHONE NO. 915-688-2584

(This space for State Use)

Orig. Signed by
Paul Kautz
Geologist

APPROVED BY _____ TITLE _____ DATE AUG 18 1993

CONDITIONS OF APPROVAL IF ANY:

THE COMMISSION MUST BE NOTIFIED 24 HOURS PRIOR TO THE BEGINNING OF PLUGGING OPERATIONS FOR THE C-103 TO BE APPROVED.

BRIDGES STATE # 196
VACUUM GRAYBURG (SAN ANDRES) FIELD
LEA COUNTY, NEW MEXICO

RECOMMENDED WORKOVER PROCEDURE

1. MIRU PU. DIG PIT. FLOW WELL BACK TO PIT. ND WH. NU BOP.
2. RIH W/ WS TO CIBP @ 4295'. LOAD HOLE W/ 10 PPG GELLED BRINE. SPOT 25 SX CLASS C NEAT CMT CAP ON TOP OF CIBP.
3. PUH TO 3000'. SPOT 20 SX CLASS C NEAT CMT PLUG ACROSS YATES TOP @ 2925' FROM 3000-2850'.
4. PUH TO 1835'. SPOT 30 SX CLASS C NEAT CMT PLUG ACROSS CSG SHOE @ 1710' & SALT TOP FROM 1835-1635'.
5. PUH TO 30'. SPOT 10 SX CLASS C NEAT CMT PLUG FROM 30'-SURFACE. POOH W/ WS.
6. ND BOP. RD PU. DIG OUT CELLAR AND CUT CSG 3' BELOW SURFACE. WELD STEEL PLATE ON CSG STUB. ERECT P&A MARKER WITH WELL NAME AND PLUGGED DATE. FILL CELLAR AND CLEAN SURFACE LOCATION.

BRIDGES STATE
WELL # 196
VACUUM GRAYBURG (SAN ANDRES) FIELD
LEA COUNTY, NEW MEXICO
CURRENT COMPLETION

GL = 4020'

C, 24, 17-S, 34-E, 1188' FNL, 1357' FWL

1710'

8-5/8" 24# K-55 ST&C CSG CMT'D W / 1400 SX CIRC.

PBTD=4755'
TD=4800'

5-1/2" ELDER CIBP @ 4295'

5-1/2" ELDER CIBP @ 4470' W/ 44' CLASS C NEAT CMT CAP

SAN ANDRES PERFS 4563-4637'

5-1/2" 14# K-55 ST&C CSG CMT'D W / 2100 SX CIRC.

BRIDGES STATE
WELL # 196
VACUUM GRAYBURG (SAN ANDRES) FIELD
LEA COUNTY, NEW MEXICO
PROPOSED COMPLETION

GL = 4020'

C, 24, 17-S, 34-E, 1188' FNL, 1357' FWL

10 SX CLASS C NEAT CMT PLUG
FROM 30'-SURFACE

8-5/8" 24# K-55 ST&C CSG @ 1710'
CMT'D W / 1400 SX CIRC.

30 SX CLASS C NEAT CMT PLUG ACROSS CSG SHOE @
1710' & SALT TOP FROM 1835-1635'

20 SX CLASS C NEAT CMT PLUG ACROSS YATES TOP @
2925' FROM 3000-2850'

25 SX CLASS C NEAT CMT CAP ON 5-1/2" ELDER CIBP @
4295'

5-1/2" ELDER CIBP @ 4470' W/ 44' CLASS C NEAT CMT CAP

SAN ANDRES PERFS 4563-4637'

5-1/2" 14# K-55 ST&C CSG CMT'D W / 2100 SX CIRC.

PBTD=4755'
TD=4800'