

U. S. GEOLOGICAL SURVEY
P. O. BOX 1880
HOBBS, NEW MEXICO 88240

DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐
2. NAME OF OPERATOR
Pennzoil Company
3. ADDRESS OF OPERATOR
P.O. Drawer 1828, Midland, TX 79701
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 510' FSL & 990' FEL, Sec 30, T-19-S,
AT TOP PROD. INTERVAL: R-34-E
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

- | REQUEST FOR APPROVAL TO: | | SUBSEQUENT REPORT OF: |
|------------------------------|--------------------------|--------------------------|
| TEST WATER SHUT-OFF | <input type="checkbox"/> | <input type="checkbox"/> |
| FRACTURE TREAT | <input type="checkbox"/> | <input type="checkbox"/> |
| SHOOT OR ACIDIZE | <input type="checkbox"/> | <input type="checkbox"/> |
| REPAIR WELL | <input type="checkbox"/> | <input type="checkbox"/> |
| PULL OR ALTER CASING | <input type="checkbox"/> | <input type="checkbox"/> |
| MULTIPLE COMPLETE | <input type="checkbox"/> | <input type="checkbox"/> |
| CHANGE ZONES | <input type="checkbox"/> | <input type="checkbox"/> |
| ABANDON* | <input type="checkbox"/> | <input type="checkbox"/> |
| (other) For Your Information | | |

5. LEASE
NM-056376
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Mescalero "30" Fed
9. WELL NO.
1
10. FIELD OR WILDCAT NAME
Quail Ridge (Morrow)
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec 30, T-19-S, R-34-E
12. COUNTY OR PARISH
Lea
13. STATE
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
GL 3650 RKB 3668

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 5-24-85 Spudded 17 1/2" Hole @ 8:30 A.M.
- 5-24-85 Drilled to 415'. Ran 13 3/8", 48# csg to 411'. Cemented w/425 sx Dowell Hi-Early Class "C" + 2 % CACL₂. Plug Down @ 11:00 P.M. Circulated 85 sx to surface.
- 5-25-85 After 18 hrs WOC. Tested csg to 800 psi - OK.
- 6-4-85 Drilled 11" Hole to 4998'. Ran 8 5/8", 24 & 28# csg to 4997'. Cemented w/2250# Class "C" + 3% D-79 + 21 #/sx salt + .5% D112 + 5#/sx Kolite tailed w/300 sx Class "C" + 1/4#/sx Celloflake. Circulated 550 sx to surface.
- 6-5-85 After 22 1/2 Hrs WOC. Tested csg to 1500 psi for 30 min. - OK.
- 6-13-85 Drilling 7 7/8" Hole @ 8653'.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Randy Hobbs TITLE PETE ENG DATE 6/13/85

(This space for Federal or State office use)

APPROVED BY ACCEPTED FOR RECORD TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

JUL 1 1985

*See Instructions on Reverse Side

CARLSBAD, NEW MEXICO

1

RECEIVED

RECEIVED

JUL - 2 1985

U.S. DEPT. OF JUSTICE
HONORARY OFFICE