

DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☐ other ☐ P&A

2. NAME OF OPERATOR

Harvey E. Yates Company

3. ADDRESS OF OPERATOR

P.O. Box 1933 Roswell, NM 88202

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 660' FSL & 660' FEL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐CHANGE ZONES ☐ABANDON* ☐(other) ☐

SUBSEQUENT REPORT OF:

☐☐☐☐☐☐☐☒

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4-6-93 Dump 50' cement on CIBP @ 8085'

4-7-93 Set CIBP @ 7650' - dump 35' cement on top.

4-8-93 Spot 50 sxs @ 1522' - 1257' - tagged - pulled 1420' of 5 1/2"

4-9-93 Spot 50 sxs @ 521' - 375' - tagged

4-9-93 Spot 16 sxs @ 61' - surface

Circulated mud

Installed dry hole marker

Approved as to plugging of the well bore.
Liability under bond is retained until
surface restoration is completed.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Jim W. Glass TITLE Engineer

DATE 4/19/93

(ORIG. SGD.) DAVID R. GLASS (This space for Federal or State office use)

APPROVED BY

TITLE

PETROLEUM ENGINEER

DATE

CONDITIONS OF APPROVAL, IF ANY:

APR 27 1993