

DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

(Other instructions on reverse side)

Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

NM-57285

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Sunburst Shogrin Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLM. AND SURVEY OR AREA

Sec 22-T19S-R34E

1. OIL WELL GAS WELL OTHER

2. NAME OF OPERATOR
Manzano Oil Corporation 505/623-1996

3. ADDRESS OF OPERATOR
P.O. Box 571/Roswell, NM 88202

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)
At surface
1860' FSL & 1980' FEL

14. PERMIT NO.
30-025-29543

15. ELEVATIONS (Show whether DV, ST, OR, etc.)
3768' GR

12. COUNTY OR PARISH 13. STATE
Lea New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF
FRACTURE TREAT
SHOOT OR ACIDIZE
REPAIR WELL
(Other)

PULL OR ALTER CASING
MULTIPLE COMPLETE
ABANDON*
CHANGE PLANS

WATER SHUT-OFF
FRACTURE TREATMENT
SHOOTING OR ACIDIZING

REPAIRING WELL
ALTERING CASING
ABANDONMENT*

(Other) Casing & Cementing

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 12/28/85 Spudded well @ 9:00 a.m. 12/28/85. Drilled 17-1/2" hole to 410'. Ran 10 joints (414.57') of 13-3/8" 54.5# casing with float, shoe & 1 centralizer. Set and cemented @ 410' with 400 sacks Class C cement with 2% CaCl. Circulated 106 sacks to surface. Plug down @ 8:15 p.m. 12/28/85. Tested to 1000#, held OK.
- 1/5/86 Drilled 12-1/4" hole to 4225'. Ran 46 joints (4262.70') of 8-5/8" 32#, 24# & 32# ST&C & J55 casing. Set and cemented at 4225' with 1400 sacks Halliburton Lite cement with 15# salt and 1/4# floseal per sack followed by 300 sacks Class C cement with 2% CaCl. Plug down @ 1:30 p.m. 1/5/86. Circulated 25 sacks to surface. Differential pressure 1300#, pressured plug to 1700#, held OK.

ACCEPTED FOR RECORD

JAN 15 1986

CARLSBAD, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED Jackie Midkiff

TITLE Jackie Midkiff/Prod. Clerk

DATE 1/9/86

(This space for Federal or State office use)

APPROVED BY _____

TITLE _____

DATE _____

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side