

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-	7. Unit Agreement Name
2. Name of Operator Amerind Oil Co.	8. Farm or Lease Name Cities Service "15"
3. Address of Operator 500 Wilco Bldg., Midland, Texas 79701	9. Well No. 1
4. Location of Well UNIT LETTER <u>L</u> <u>1980</u> FEET FROM THE <u>South</u> LINE AND <u>660</u> FEET FROM THE <u>West</u> LINE, SECTION <u>15</u> TOWNSHIP <u>17S</u> RANGE <u>37E</u> MAPM.	10. Field and Pool, or Wildcat Humble City Strawn
15. Elevation (Show whether DF, RT, GR, etc.) 3748' GL, 3762' KB	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

'Surface casing: February 25, 1986 - Ran 411.83' 13-3/8" 54.5# & 61# csg w/3 centralizers & guide shoe. Set @ 406'. Circ 135 sx. PD 10:00 P.M. MST 2/25/86. Rule 107 - Option 2: 1) 528 cu ft Southwestern El Toro cmt. 400 sx Cls "C" w/2% CaCl₂. 2) Approx temp of slurry when mixed 70°F. 3) Est min formation temp 70°F. 4) Est cmt strength @ time of test 810 psi. 5) Time in place 12 hrs.

Intermediate casing: March 3, 1986 - Ran 8-5/8" csg as follows:

Guide shoe	1.20'
1 jt 8-5/8" 32# S-80	39.62'
Float collar	1.70'
11 jts 8-5/8" 32# S-80	465.77'
64 jts 8-5/8" 32# J-55	2028.96'
35 jts 8-5/8" 24# J-55	1972.24'
Total string	4509.49'

Set @ 4500'. PD 12:45 P.M. MST 3/3/86. Circ 175 sx. Ran fluid caliper. Rule 107 - Option 2: 1) 4096 cu ft Southwestern El Toro cmt. Pumped 1850 sx Lite w/6# salt & 1/4# Flocele/sk, & 300 sx Cls "C". 2) Approx temp of slurry when mixed 70°F. 3) Est min formation temp 95°F. 4) Est cmt strength @ time of test 830 psi. 5) Time in place 12 hrs.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Robert C. Leibrock TITLE Vice President DATE March 5, 1986

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT I SUPERVISOR

APPROVED BY _____ TITLE _____ DATE MAR 10 1986

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED
MAR 7 - 1986
O.C.D.
HOBBS OFFICE