

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.
30-025-29660

5. Indicate Type of Lease
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

Lea Farms

8. Well No.
#2

9. Pool name or Wildcat
So. Humble City, Strawn

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
--OIL WELL ☐ OAS WELL ☒ OTHER

2. Name of Operator
Bonneville Fuel Corporation

3. Address of Operator
1660 Lincoln, Suite 1800, Denver, CO 80264

4. Well Location
Unit Letter H : 1800 Feet From The North Line and 500 Feet From The East Line

Section 14 Township 17S Range 37E NMPM Lea County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3727 GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☒

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

4/14/97 MIRU. RIH, tagged RBP @10,680'. Spot 2 sx sd on 5 1/2" RBP. Spot Plug #1 of 25 sx Cl-H cmt (15.6 ppg; 1.18 yld) @ 10,640'. Hoco calc TOC @ 10395'. LD 70 jts 2 7/8" tbq. Pumped 130 bbls gelled mud between 5 1/2" & 9 5/8" csg. Spot Plug #2 of 20 sx Cl-H cmt @ 8452' in 5 1/2" csg (15.6 ppg; 1.18 yld), Hoco calc TOC @ 8252'. Spot plug #3 of 20 sx Cl-H cmt @ 7023' (15.6 ppg; 1.18 yld), Hoco cal TOC @ 6825'. Cut off 5 1/2" csg @ 4720' LD 123 jts. Load hole w/96 bbls gelled brine wtr. Spot plug #4 of 75 sx Cl-C cmt + 3% cacl2 (14.8ppg; 1.33 yld) Hoco calc TOC @ 4540'. WOC. RIH, didn't tag plug. Spot additional 75 sx Cl-C cmt + 1/2#/sx flocele + 5# gilsonite + 2% cacl2 (14.8 ppg; 1.39 yld) @ 4767'. WOC.
4/16/97 Tag plug @ 4680'. Spot plug #5 of 50 sx Cl-C cmt + 3% cacl2 @ 4677' (14.8ppg; 1.33 yld). Tag plug @ 4527'. Spot plug #6 of 35 sx Cl-C cmt @ 2213' in 9 5/8" csg, Hoco calc TOC @ 2094'. Pump plug #7 of 10 sx Cl-C cmt 30' to surface (14.8 ppg; 1.32 yld). Installed Dry Hole Marker & cleaned location. Plugged & Abandoned well 4/17/97.

Bonneville Fuels will notify NMOCD as soon as the location restoration is complete and ready for inspection.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Doris Maly TITLE Engineering Tech. DATE 5/07/97

TYPE OR PRINT NAME Doris Maly TELEPHONE NO. 303 863-1555

(This space for State Use)

APPROVED BY Jack Griffin TITLE OIL & GAS INSPECTOR DATE JUN 26 1998

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED
1997
Hobbs
DCC