

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPlicate
Other Instructions
Form 3160-5

BLM Form No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. LEADS DESIGNATION AND SERIAL NO.
NM-9017
2. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. UNIT ABBREVIATION NAME
4. FIRM OR LEASE NAME
Conoco Federal
5. WELL NO.
2
6. FIELD AND POOL, OR WILDCAT
Shugart SR Queen Grayburg
7. SEC., T., R., E., OR B.E. AND
SURVEY OR AREA
Sec. 18: T18S, R32E
8. COUNTY OR PARISH
Lea
9. STATE
NM

10. WELL TYPE
OIL WELL ☒ GAS WELL ☐ OTHER

11. NAME OF OPERATOR

Siete Oil & Gas Corporation

12. ADDRESS OF OPERATOR

P. O. Box 2523, Roswell, NM 88201

13. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
(See also space 17 below.)
At surface

400' FSL, 400' FWL, SW/4 SW/4

14. PERMIT NO.

15. ELEVATIONS (Show whether SW, NT, OR, etc.)

3720' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANE

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Production Casing

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

X

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

12/21/86 - Drlg @4450' - formation dolomite & sand - mud wt. 10.1 - visc 28 - brine & native mud - T.D. 4500' @1:45 a.m. - circ & cond mud 1½ hrs - TOH laying down DP & DC - RU & ran 112 jnts 5½" 15# LT&C csg (4522') set @4500'KB - cmted w/800 sx Dowell Lite Wt. III, 8# salt, ¼# celloflake, .5% D59 - tailed in w/300 sx standard, 5# salt, .5% D59 - P.D. @2:00 p.m. - circ 50 sx to pit - set slips & cut off 5½" csg - dev survey: ½° @4500' - Release L & M Rig #1 @4:00 p.m. - W.O.C.

ACCEPTED FOR RECORD

JAN 7 1987

jm

CARLSBAD, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

L. D. Justice

TITLE V.P. Drilling & Production

DATE 12/22/86

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side