

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPL
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Harvey E. Yates Company

3. ADDRESS OF OPERATOR

P.O. Box 1933 Roswell, New Mexico 88201

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)

At surface

560' FSL & 2310' FWL

Unit N

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3897.5 GL

5. LEASE DESIGNATION AND SERIAL NO.

NM 22085

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Amoco 1 Federal

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

N. Young-Bone Spring

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec 1 T-18S R-32E

12. COUNTY OR PARISH

Lea

13. STATE

N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Spud, Surface & Intermediate Report X

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

2-8-87 Spud well @ 12:01PM

2-9-87 Ran 433' of 13 3/8, 54.5, J-55 Csg Set @ 428.
Cement w/ 450 sks class 'C' w/2% CaCl₂ & 1/4 #/ Floceal.

2-12-87 Ran 2905 ft. of 8 5/8 24#, J55 Csg set @ 2900'.
Cement w/ 1150 sk DLW III & 200 sks class 'C'

Circl. 185 sks to pit. WOC-12 Hours & test Csg & BOP 1200psi/30min-Held

18. I hereby certify that the foregoing is true and correct

SIGNED N.M. Young

TITLE Drilling Superintendent

DATE 2-13-87

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACCEPTED FOR RECORD
DATE

FEB 17 1987

*See Instructions on Reverse Side

CARLSBAD, NEW MEXICO