

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRI
(Other instruction
verse side)

ATD
as re-

Expires August 31, 1985

SUNDY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

1. NAME OF OPERATOR

Siete Oil & Gas Corporation

2. ADDRESS OF OPERATOR

P. O. Box 2523, Roswell, NM 88201

3. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)

(See also space 17 below.)
At surface

1650' FNL & 1650' FWL ^{SE} SW/4 NW/4

14. PERMIT NO.

15. ELEVATIONS (Show whether BP, ST, GR, etc.)

3712 GR

5. LEASE DESIGNATION AND SERIAL NO.

NM 67987

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Jade Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

East Shugart Delaware

11. SEC., T., R. & S. OR BLM. AND
SURVEY OR AREA

Section 19: T18S, R32E

12. COUNTY OR PARISH 13. STATE

Lea

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANE

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACURE TREATMENT

SHOOTING OR ACIDIZING

(Other) cement surface casing

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

XX

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

6/20/87 L & M rig #1 spudded surface hole @ 1:30 p.m. - TD 12 1/4" hole to 376' @ 6:00 p.m. - ran 9 jts. of 8 5/8" 23# csg. - set @ 372' KB & cemented w/230 sks. Dowell Hi Early II containing 2% CaC₂ & 1/4# D-29 - plug down @ 8:00 p.m. - circulated 35 sks. to pit.

6/21/87 RU BOP & tested to 1000 PSI - held ok.

ACCEPTED FOR RECORD

JUN 24 1987

SJS

CARLSBAD, NEW MEXICO

RECEIVED

JUN 23 11 29 AM '87

CARLSBAD RESOURCE
AREA HEADQUARTERS

18. I hereby certify that the foregoing is true and correct

SIGNED

H.D. Just

TITLE Drlg. & Prod. Vice Pres.

DATE

6/22/87

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side