

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPlicate
(Other instructions on
reverse side)

Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

1. NAME OF OPERATOR

Siete Oil & Gas Corporation

2. ADDRESS OF OPERATOR

Post Office Box 2523, Roswell, New Mexico 88201

3. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

1700' FNL & 330' FWL, SW/4 NW/4, Unit Letter E

14. PERMIT NO.

15. ELEVATIONS (Show whether NF, HT, GR, etc.)

4. LEASE DESIGNATION AND SERIAL NO.

NM - 9016

5. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT ASSIGNMENT NAME

8. FARM OR LEASE NAME

Inca Federal

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

East Shugart Delaware

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 19: T18S, R32E

12. COUNTY OR PARISH

Lea

13. STATE

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACURE TREAT

MULTIPLE COMPLETION

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANE

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other) cementing surface casing

x

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

6/8/87 L & M Rig #1 spudded 12 1/4" hole @ 7:45 a.m.
T. D. to 378' @ 11:45 a.m.
Ran 8 jts. of 8 5/8" 23# csg. (376') set @ 372' K.B.,
cemented w/225 sks. H E II cement 2% CaCl₂, 1/4# D-29,
circulated 35 sks. to pit. Plug down @ 7:30 p.m.

W. O. C. 18 hrs.

6/9/87 Tested BOP to 1000 PSI for 30 minutes - held ok.

ACCEPTED FOR RECORD

JUN 11 1987

SJS

CARLSBAD, NEW MEXICO

RECEIVED
JUN 11 11 02 AM '87
CARLSBAD RESOURCE
AREA HEADQUARTERS

18. I hereby certify that the foregoing is true and correct

SIGNED

H. D. Justice

TITLE Drlg. & Prod. Vice Pres. DATE 6/10/87

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side