

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPlicate  
(Other Instructions  
over side)

Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Siete Oil & Gas Corporation

3. ADDRESS OF OPERATOR

P. O. Box 2523, Roswell, NM 88201

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)  
At surface

660' FNL & 1650' FWL NE/4 NW/4

16. PERMIT NO.

15. ELEVATIONS (Show whether DV, RT, GR, etc.)

3717' GR

5. LEASE DESIGNATION AND SERIAL NO

NM-9016

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Inca Federal

9. WELL NO.

3

10. FIELD AND POOL, OR WILDCAT

East Shugart Delaware

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 19: T18S, R31E

12. COUNTY OR PARISH

Lea

NM

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANE

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Production Casing

(Note: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

7/22/87 L & M Rig #1 TD 7 7/8" hole to 5500' @ 11:30 p.m.

7/23/87 Schlumberger ran CNL/LDT, Calip, DLL/MSFL, EPT, FMS.

7/24/87 L & M Rig #1 ran 133 jts. 5 1/2" 15.5# J-55 casing (5532.08') set @ 5500' KB. Cemented in two stages w/DV Tool @ 2957'. 1st stage 590 sks. Dowell Std. 3# salt, .5% D-127 Flac. Circulated 50 sks. to pit. 2nd stage 770 sks. 35/65 Litepoz, 8% salt, 1/4# D-29. Circulated 35 sks. to pit.

ACCEPTED FOR RECORD

AUG 10 1987  
SJS

CARLSBAD, NEW MEXICO

AUG 6 11 30 AM '87  
CARLSBAD FIELDHOUSE  
AREA HEADQUARTERS

RECEIVED

18. I hereby certify that the foregoing is true and correct

SIGNED

*H. L. Sauter*

TITLE Drlg. & Prod. Vice Pres. DATE 7/29/87

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side

RECEIVED  
AUG 12 1957  
OCE  
MAILS OFFICE