

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-71

5a. Indicate Type of Lease
State ☒ Fee ☐

5. State Oil & Gas Lease No.
B-155

SUNDRY NOTICES AND REPORTS ON WELLS
DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.

1. ☒ OIL WELL ☐ GAS WELL ☐ OTHER	7. Unit Agreement Name Central Vacuum Unit
2. Name of Operator Texaco Producing Inc.	8. Farm or Lease Name
3. Address of Operator P.O. Box 728 Hobbs, NM 88240	9. Well No. 266
4. Location of Well UNIT LETTER <u>H</u> <u>1971</u> FEET FROM THE <u>North</u> LINE AND <u>1310</u> FEET FROM <u>East</u> THE <u>36</u> LINE, SECTION <u>17-S</u> TOWNSHIP <u>34-E</u> RANGE <u>34-E</u> N.M.P.M.	10. Field and Pool, or Wildcat Vacuum Grayburg San Andres
15. Elevation (Show whether DF, RT, GR, etc.) 3993' GR	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPWS. ☐
CASING TEST AND CEMENT JOB ☒
OTHER ☐
ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spud 24" hole at 10:00 am 8-31-87. Drilled to TD 352'. Ran 9 jts. 20", 133#, J55 Buttress csg and set at 352'. Cemented w/ 1000 sxs class H w/ 2% CaCl₂ and 1/4" cellocele. Circ 313 sxs. Drilled out float collar. Tested csg to 600#, 11:30 pm - 12:00 pm 9-3-87

Drilled 17 1/2" hole to 1550'. Ran 36 jts. 13 3/8", 54.5#, K55, ST+C, set at 1550'. Cemented w/ 1200 sxs. class 'H' lite w/ 2% CaCl₂ and 1/4" cello seal followed by 250 sxs 'H' w/ 2% CaCl₂ and 1/4" cello seal. Circ. 297 sxs. Drilled out to csg shoe. Tested csg to 1000# 6:00 - 6:30 pm 9-7-87.

(CONT'D ON BACK)

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED A. Gernandt TITLE Area Superintendent DATE 9-17-87

A. Gernandt 393-4031

ORIGINAL SIGNED BY JERRY SEXTON

APPROVED BY DISTRICT 1 SUPERVISOR

DATE SEP 21 1987

CONDITIONS OF APPROVAL, IF ANY:

Drilled 12 1/4" hole to 2844'. Reduced bit to 8 3/4" and drilled to 4300'.
Ran 101 jts. 7", 23#, JSS, LT+C csg and set at 4300'. Cemented w/
1750 sxs class 'H' lite w/ 15# salt + 1/4# celloseal followed by 250 sxs
class 'H' w/ 1/4# celloseal. Circ 470 sxs. Drilled out. Tested csg
to 1500# 12:15 am - 12:45 am 9-15-87.

RECEIVED

SEP 18 1987

OCD
HOESS OFFICE