

DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

1. NAME OF OPERATOR

Siete Oil and Gas Corporation

2. ADDRESS OF OPERATOR

P. O. Box 2523 Roswell, New Mexico 88202

3. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

760' FNL & 430' FWL NW/4 NW/4 Unit Letter D

14. PERMIT NO.

API # 30-025-30039

15. ELEVATIONS (Show whether DF, ST, OR, etc.)

3711' GR

6. LAND DESIGNATION AND SERIAL NO.

NM 9016

7. OF INTEREST, APPLICABLE TO THIS WELL

8. WELL CLOSURE STATUS

9. NAME OF LAND OWNER

Inca Federal

10. WELL NO.

4

11. SURFACE AND POOL, OR WILDCAT

Y-SR-Q-RB-SA

12. SURFACE, OR WILDCAT, OR SURFACE AND POOL

Sec. 19: T18S, R32E

13. COUNTY OR PARISH

Lea

14. STATE

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

WELL OR ALTER CASING

MULTIPLE COMPLETS

ABANDON*

CHANGE PLANE

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Casing

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and names pertinent to this work.) *

1/14/88 L & M Rig #1, reached T.D. - 4500' @ 9:15 p.m.

1/15/88 Ran 109 jts. (4504.29') 5 1/2", 15.5#/ft. J-55 casing, set @ 4500' KB. Cemented w/800 sks. 35/65 POZ w/6% gel, 8% salt and 1/4#/sk.-Celloflake, tail in w/250 sks. Dowell standard, w/0.5% D-127 additive and 5% salt. Circulate 15 sks. to the pits. Plug down at 11:30 a.m. on 1/15/88.

ACCEPTED FOR RECORD

FEB 1 1988

SJS
CARLSBAD, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Production/Reservoir Engineer DATE 1/21/88

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side