

UNITED STATES DEPARTMENT OF THE INTERIOR (Other Instructions on Reverse Side)
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

1. NAME OF OPERATOR
Siete Oil and Gas Corporation

2. ADDRESS OF OPERATOR
P. O. Box 2523 Roswell, 1 New Mexico 88202

3. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surface

1980' FWL, 660' FNL NE/4 NW/4 Unit Letter C

4. PERMIT NO.
30-025-30061

5. ELEVATIONS (Show whether SV, HT, OR, etc.)
3768' GR

6. LEASE INFORMATION AND SERIAL NO.
NM 9016

7. IF LEASE, ALLOTTEE OR TRUST NAME

8. SURVEY ASSASSMENT NAME

9. NAME OF LEASE NAME
Inca Federal

10. WELL NO.

7

11. FIELD AND POOL, OR WILDCAT
Young North (Bone Spring)

12. SEC., T., R., N., OR S.W., AND
SUBST. OF AREA

Sec. 17: T18S R32E

13. COUNTY OR PARISH
Lea

14. STATE
NM

15. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF
FRACTURE TREAT
SHOOT OR ACIDIZE
REPAIR WELL
(Other)

RELL OR ALTER CASING
MULTIPLE COMPLETE
ABANDON*
CHANGE PLANE

SUBSEQUENT REPORT OF:

WATER SHUT-OFF
FRACTURE TREATMENT
SHOOTING OR ACIDIZING
(Other)

REPAIRING WELL
ALTERING CASING
ABANDONMENT*

5 1/2" Production

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

12/24/87 W.E.K. Rig #2 T. D. 7 7/8" Hole to 9300'

12/26/87 Ran 224 Jts. 5 1/2" 15.5# & 17# Casing (9300.5'). Set @ 9300' KB. Cemented in 2 stages w/DV Tool @ 4378'.

1st stage - Cemented w/1460 sks. Standard w/.5% FLA, .2% Retarded 5# Salt. Circulated 100 sks. to pit. Plug down @ 1:30 a.m.
12/27/87.

12/27/87 2nd Stage - Cemented w/750 sks. 35/65 POZ, 6% D-20, 8# salt, 1/4# D-29. Tail in w/170 sks. Standard, 5# salt, .5% FLA, Plug down @ 9:15 a.m. Circulated 100 sks. to pit. W.O.C.

ACCEPTED FOR RECORD

JAN 22 1988

SJS
CARLSBAD, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

H.O. Justice

TITLE

V.P. Drilling and Production

DATE

12/28/87

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side