

ILLEGIBLE

PENNZOIL COMPANY
STATE WELL NO. 2-1
WT-LL125

DATE
11/12/34
35/10/31

MEASURED	INCL.	HOLE	COURSE	TRUE	VERTICAL	RECTANGULAR	C L O S U R E	DUG-LEG
DEPTH	ANGLE	DIRECTION	LENGTH	DEPTH	SECTION	COORDINATES	DISTANCE	SEVERITY
FEET	DEGS.	DEGS.	FEET	FEET	FEET	N/S feet E/W	FEET	DEGS.

9661.00	12.25	S 38.00 W	94.00	9650.30	110.72	49.34 S	112.05 W	122.43' S 56.24 W	1.35
9755.00	13.50	S 39.00 W	94.00	9741.94	131.65	55.73 S	125.09 W	141.31' S 62.39 W	1.30
9849.00	14.75	S 38.00 W	94.00	9833.09	154.56	83.68 S	139.37 W	162.56' S 59.02 W	1.30
9944.00	14.50	S 39.00 W	95.00	9925.01	178.53	102.45 S	154.30 W	185.22' S 56.42 W	1.30
10039.00	14.75	S 40.00 W	94.00	10015.97	202.25	120.77 S	169.40 W	209.04' S 54.51 W	1.30
10132.00	15.00	S 39.00 W	94.00	10106.02	226.38	131.39 S	184.75 W	231.43' S 52.97 W	1.30
10227.00	15.00	S 38.00 W	95.00	10198.58	250.94	150.63 S	200.05 W	253.31' S 51.59 W	1.30
10321.00	14.75	S 38.00 W	94.00	10239.43	275.04	171.64 S	214.91 W	273.82' S 50.42 W	1.30
10415.00	14.75	S 38.00 W	94.00	10380.33	298.84	192.50 S	229.64 W	302.24' S 49.45 W	1.30
10510.00	15.00	S 39.00 W	95.00	10472.15	323.30	215.59 S	244.82 W	323.22' S 48.63 W	1.30
10604.00	14.50	S 39.00 W	94.00	10563.05	347.82	234.99 S	259.89 W	349.83' S 47.98 W	1.30
10698.00	15.00	S 40.00 W	94.00	10653.95	371.15	252.65 S	275.11 W	371.52' S 47.14 W	1.30
10793.00	15.00	S 39.00 W	95.00	10745.72	395.73	271.83 S	290.75 W	397.89' S 46.95 W	1.30
10887.00	14.00	S 39.00 W	94.00	10836.72	419.25	294.92 S	305.56 W	421.21' S 45.58 W	1.30
10981.00	12.00	S 37.00 W	94.00	10928.31	440.35	305.38 S	318.58 W	442.13' S 45.10 W	1.30
11076.00	10.50	S 39.00 W	95.00	11021.40	458.87	321.18 S	329.99 W	460.49' S 45.17 W	1.30
11170.00	9.00	S 41.00 W	94.00	11114.12	474.78	331.38 S	340.22 W	474.33' S 45.06 W	1.30
11264.00	7.50	S 45.00 W	94.00	11207.14	488.25	343.24 S	349.41 W	489.80' S 45.51 W	1.30
11358.00	5.75	S 49.00 W	94.00	11300.42	499.85	351.19 S	357.94 W	501.45' S 45.55 W	1.30
11397.78	6.67	S 50.88 W	29.79	11350.00	503.29	353.43 S	360.60 W	504.92' S 45.56 W	1.30
11410.00	6.61	S 52.28 W	22.22	11352.06	505.82	355.02 S	362.62 W	507.48' S 45.61 W	1.30
11453.00	6.50	S 55.00 W	43.00	11394.79	510.61	357.94 S	366.57 W	512.34' S 45.58 W	1.30
11547.00	6.75	S 55.00 W	94.00	11488.16	521.13	364.16 S	375.45 W	523.94' S 45.58 W	1.30
11552.00	6.76	S 55.32 W	5.00	11493.12	521.70	361.49 S	375.94 W	523.62' S 45.59 W	1.30
11606.00	6.91	S 58.77 W	54.60	11546.74	527.37	367.99 S	381.33 W	529.93' S 46.42 W	1.30