

MEASURED INCL. ANGLE DEGS. HOLE DIRECTION DEGS. TRUE VERTICAL DEPTH FEET VERTICAL SECTION FEET RECTANGULAR COORDINATES N/S E/W DISTANCE FEET DEGS. DUG-LEG SEVERITY

11634.00	6.98	S 60.55 W	28.00	11574.53	531.08	369.70	S	384.25	W	533.22	S	46.11	W	.82
11641.00	7.00	S 61.00 W	7.00	11581.48	531.88	370.11	S	384.99	W	534.04	S	46.13	W	.82
11687.00	6.52	S 63.42 W	46.00	11627.16	536.93	372.64	S	389.78	W	539.25	S	45.29	W	1.22
11736.00	6.00	S 66.00 W	49.00	11675.87	541.81	374.92	S	394.61	W	544.32	S	45.47	W	1.20
11761.00	5.80	S 65.47 W	25.00	11700.74	544.15	375.97	S	396.95	W	546.74	S	45.55	W	.93
11830.00	5.25	S 64.00 W	69.00	11769.41	550.23	378.81	S	402.96	W	553.06	S	45.77	W	.82
11860.00	5.25	S 64.00 W	30.00	11799.29	552.75	386.01	S	405.43	W	555.68	S	46.85	W	0.80

FINAL STATION IS PROJECTED

CLOSURE DISTANCE =
CLOSURE DIRECTION =

555.68 FEET
S 46.85 W

