

November 1983)
Formerly 9-331)

UNITED STATES DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
NOTES, NEW MEXICO

EXPIRES AUGUST 31, 1987

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

1. NAME OF OPERATOR

Siete Oil & Gas Corporation

2. ADDRESS OF OPERATOR

P. O. Box 2523 Roswell, New Mexico 88202

3. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

1650' FWL & 2310' FSL NE/4 SW/4

14. PERMIT NO.

API - 30-025-30111

15. ELEVATIONS (Show whether M., FT., OR, ETC.)

3709' GR

4. LAND DESIGNATION AND SERIAL NO.

NM-9019

5. IF APPLICABLE, ALLOTMENT OR TRACT NAME

6. NAME OF LAND OWNER

Mohawk Federal

7. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

East Shugart Delaware

11. SEC., T., R., OR NE., AND SURVEY OR ADJAC.

Sec. 19: T18S R32E

12. COUNTY OR PARISH

Lea

13. STATE

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐
☐

PLUG OR ALTER CASING

☐
☐
☐
☐
☐

FRACTURE TREAT

MULTIPLE COMPLETION

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANE

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐
☐
☐
☐
☐

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Production Casing

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

☐
☐
☐
☐
☐

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

11/8/87 - L & M Rig #1 T.D. 7 7/8" hole to 6550' @ 11:30 a.m.

11/9/87 - Ran 161 jts. 5 1/2 - 15.5# LT & C Casing (6558') set @ 6550' KE - stage tool @ 3947'.

Cemented first stage w/665 sks. 25/75 POZ - .7# Salt - .5% FI D127, Circulated 50 sks. to pit.

Cemented second stage w/970 sks. 35/65 POZ - 8# Salt - 6% Gel - 1/4# Celloflake - circulated 30 sks. to pit.

ACCEPTED FOR RECORD

NOV 17 1987

SJS

18. I hereby certify that the foregoing is true and correct

SIGNED

V. P. Drilling & Production

TITLE V. P. Drilling & Production

DATE 11/11/87

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

RECEIVED
NOV 18 1987
OCD
HOBBY OFFICE