

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION

P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-73

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
V-1793	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT - I" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name	
2. Name of Operator Yates Petroleum Corporation		8. Farm or Lease Name Lee Ranch AEZ State	
3. Address of Operator 105 South 4th St., Artesia, NM 88210		9. Well No. 1	
4. Location of Well UNIT LETTER <u>A</u> <u>990</u> FEET FROM THE <u>North</u> LINE AND <u>330</u> FEET FROM THE <u>East</u> LINE, SECTION <u>35</u> TOWNSHIP <u>17S</u> RANGE <u>35E</u> NMPM.		10. Field and Pool, or Wildcat Wildcat	
15. Elevation (Show whether DF, RT, GR, etc.) 3898.6' GR		12. County Lea	

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <u>Spud well, set surface pipe</u> <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

Spudded 17-1/2" hole 7:30 AM 12-21-87. Ran 9 joints 13-3/8" 54.5# J-55 casing set 396'. 1-Texas Pattern Notched guide shoe set 396, insert float 351'. Cemented w/400 sx Class "C" with 2% CaCl2 (Yield 1.32, weight 14.8). PD 3:45 PM 12-21-87. Bumped plug to 500 psi, released pressure and float held okay. Cement circulated 62 sacks to pit. Drilled out at 4:45 AM 12-22-87. WOC 13 hrs. Cut off and welded on flow nipple. Reduced hole to 11". Drilled plug and resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED: [Signature] TITLE: Production Supervisor DATE: 12-22-87

ORIGINAL SIGNED IN EVERY SECTION  
DISTRICT ENGINEER

APPROVED BY: \_\_\_\_\_ TITLE: \_\_\_\_\_ DATE: DEC 28 1987

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

DEC 23 1987

CDU  
HONORARY OFFICE