

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

L CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	
7. Unit Agreement Name	
8. Farm or Lease Name	
SIMMONS ESTATE	
9. Well No.	
1	
10. Field and Pool, or Wildcat	
SHIPP STRAWN	
12. County	
LEA	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator
PENNZOIL COMPANY
3. Address of Operator
P. O. Drawer 1828 Midland, Texas 79702-1828
4. Location of Well
UNIT LETTER <u>N</u> 1980 FEET FROM THE <u>West</u> LINE AND <u>1310</u> FEET FROM
THE <u>South</u> LINE, SECTION <u>3</u> TOWNSHIP <u>17-S</u> RANGE <u>37-E</u> NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)

3764.8 GR - 3782.3 KB

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

12-27-87: Drilled 11" hole to T.D. 4210'. Ran and set 8 5/8", 28#, S-80, 8 rd
STC casing at 4210'. Cemented with 840 gals Surebond, 1300 sxs Pacsetter
Lite w/6% gel and 3# Hi-Seal per sx mixed at 12.41 ppg plus 300 sx
Class "C" cement mixed at 14.78 ppg. Plug down at 10:30 PM CST 12-26-87.
Circulated out est. 178 sx cement.

12-28-87: W.O.C. 18 hours. Tested 8 5/8" casing to 1500# for 30 mins. Held
OK. Commenced drilling 7 7/8" hole.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Ray R. Johnson
Orig. Signed by
Paul Kautz
Geologist

TITLE PRODUCTION ACCOUNTANT

DATE 1-8-88

APPROVED BY _____

TITLE _____

DATE JAN 11 1988

CONDITIONS OF APPROVAL, IF ANY: