

WRS COMPLETION REPORT

COMPLETIONS SEC 18 TWP 17S RGE 34E
PI# 30-T-0017 10/03/88 30-025-30223-0000 PAGE 1

NMEX LEA * 1980FNL 660FWL SEC SW NW
STATE COUNTY FOOTAGE SPOT
DCB O&G D DO
OPERATOR WELL CLASS INIT FIN

1 Mescalero "A" STATE
WELL NO LEASE NAME
4138KB 4120GR VACUUM
OPER ELEV FIELD POOL AREA

API 30-025-30223-0000
LEASE TYPE NO PERMIT OR WELL ID NO

02/21/1988 09/17/1988 ROTARY OIL
SPUD DATE COMP DATE TYPE TOOL STATUS
11800 GRBG-SAD MORANCO 7 RIG SUB 17
PROJ DEPTH PROJ FORM CONTRACTOR
DTD 11675 PB 4745 FM/TD CANYON
DRILLERS TD LOG TD PLUG BACK ID OLD TD FORM TD

LOCATION DESCRIPTION

9 MI E MALJAMAR, NM

WELL IDENTIFICATION/CHANGES

OPER CHGD FROM TAHOE ENERGY
FIELD CHGD FROM LEAMEX
PROJ FM CHGD FROM PENNSYLVANIAN

CASING/LINER DATA

CSG 13 3/8 @ 393 W/ 400 SACKS
CSG 8 5/8 @ 4774 W/ 1950 SACKS
PLUGS @ 11350-11450 W/40 SX, 11000-11100 W/40 SX,
9800-9900 W/40 SX, 8100-8200 W/40 SX, 5000-5300 W/150
SX

TUBING DATA

TBG 2 7/8 AT 4629

INITIAL POTENTIAL

IPP 14BOPD 3 MCFD 6BW 24HRS
GRAYBURG PERF 4533- 4581 GROSS
SN ANDRS PERF 4654- 4675 GROSS
GTY 31.1 GOR 248
FIELD /RESERVOIR
/GRAYBURG-SAN ANDRES
COMMINGLED

CONTINUED IC# 300257005488

COMPLETIONS
 PI# 30-T-0017 10/03/88 SEC 18 TWP 17S RGE 34E
 30-025-30223-0000 PAGE 2

DCB O&G
 1

MESCALERO "A" STATE

D DO

TYPE	FORMATION	LTH	TOP	DEPTH/SUB	BSE	DEPTH/SUB
LOG	RUSTLER		1549	2589		
LOG	SALT		1660	2478		
LOG	YATES		2850	1288		
LOG	QUEEN		3830	308		
LOG	GRAYBURG		4449	-311		
LOG	SN ANDRS		4603	-465		
LOG	GLORIETA		6047	-1909		
LOG	PADDOCK		6130	-1992		
LOG	TUBB		7520	-3382		
LOG	ABO		8143	-4005		
LOG	WOLFCAMP		9850	-5712		
LOG	CISCO		11060	-6922		
LOG	CANYON		11400	-7262		

SUBSEA MEASUREMENTS FROM KB

FORMATION TEST DATA

DST 1 10460-10517 WOLFCAMP
 REC 2373.0 FT SGCFLUD
 IFP 130 FFP 130
 ISIP 223 1H FSIP 241 1H30M IHP 4945 FHP 4945
 DP REC - SGCFLUD W/OIL ODOR
 HOLE IN DP
 NO OTHER DETAILS

DST 2 11033-11215 CISCO
 REC 600.0 FT MUD 89.0 FT OCM
 REC 2400.0 CC SOCM 1.0 CFT GAS
 IFP 153
 IFP 225 FFP 409
 ISIP 4904 FSIP 4482 IHP 5616 FHP 5516
 NO OTHER DETAILS

PRODUCTION TEST DATA

SN ANDRS OPENHOLE 4774- 5000
 OPEN 4774- 5000
 ACID 4774- 5000 4000GALS
 SWFR 4774- 5000 40000GALS 70000LBS SAND
 BRPG @ 4745 4774- 5000

CONTINUED