

DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

NM-9019

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different formation.  
Use "APPLICATION FOR PERMIT" for such proposals.)

WELL ☒ GAS ☐ OTHER ☐

NAME OF OPERATOR

Siete Oil & Gas Corporation

ADDRESS OF OPERATOR

P.O. Box 2523 Roswell, New Mexico 88202

LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 32 below.)

At section 1980' FEL & 660' FNL, NE $\frac{1}{4}$ NW $\frac{1}{4}$

1. SURF. ADJUDICANT NAME

2. NAME OF LEASE NAME

Lakota Federal

3. WELL NO.

1

10. STRATA AND POOL, OR WILDCAT

North Young Bone Spring Deep

11. SEC. T., R., E., OR S.E. AND  
QUARTER OR AREA

Sec. 17: T18S, R31E

12. COUNTY OR PARISH

Lea

13. STATE

NM

14. PERMIT NO.

30-025-30313

15. ELEVATIONS (Show whether M., FT., OR CM.)

3780' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐  
☐  
☐  
☐  
☐

PULL OR ALTER CASING

☐  
☐  
☐  
☐  
☐

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANE

SUBSEQUENT REPORT ON:

WATER SHUT-OFF

☐  
☐  
☐  
☐  
☐

FRACURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Spud - Surf. Csg. & Inter. Csg. X  
(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

☐  
☐  
☐  
☐  
☐

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and space pertinent to this work.)

6/03/88 WEK Rig #2 Spudded 17 $\frac{1}{2}$ " surface hole @ 12:30 PM & TD 17 $\frac{1}{2}$ " hole to 486' @ 12:00 midnight.

6/04/88 Ran 12 jts. 13 3/8" 48# ST&C casing 487.4' set @ 486' KB, cemented w/550 sks. HEII + 2% S1 +  $\frac{1}{4}$ # D-29, circ. 50 sks. to pit, plug down @ 5:45 AM.

6/05/88 Wek Rig #2 TD 12 $\frac{1}{4}$ " hole @ 10:50 PM to 2450'.

6/06/88 Ran 58 jts. 8 5/8" 24# J-55 ST&C casing 2458.78' set @ 2449' KB, cemented w/600 sks. 35/65 POZ + 6% D-20 + 8# D-44 +  $\frac{1}{4}$ # D-29, tailed in w/200 sks. HEII + 2% S1 +  $\frac{1}{4}$ # D-29, plug down @ 8:00 AM, circ. 20 sks. to pit.

JUN 3 12 42 PM '88

RECEIVED

18. I hereby certify that the foregoing is true and correct

SIGNED

*L.D. Justice*

TITLE

V.P. Drilling/Production

DATE

June 8, 1988

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

JUL 21 1988

\*See Instructions on Reverse Side

CARLSBAD, NEW MEXICO