

BUREAU OF LAND MANAGEMENT

NM-9016

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug wells in a Federal or State land. APPLICATION FOR PERMIT - see back page) RECEIVED 8824

ON ☒ DAY ☐ WEEK ☐ OTHER

NAME OF OPERATOR

Siete Oil & Gas Corporation

ADDRESS OF OPERATOR

P.O. Box 2523

Roswell, NM 88202-2523

LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)

At surface 330' FNL & 990' FWL, NW $\frac{1}{4}$ NW $\frac{1}{4}$, Unit Letter D

16. PHONE NO

30-025-30314

17. ELEVATIONS (Show whether of, to, or on, etc.)

3761' GR

18. IF OTHER, EXPLAIN (in space below)

19. DATE OF REPORT DATE

20. NAME OF LAND DATE

'Inca Federal

21. WELL NO.

9

22. NAME AND NO. OF WELLS AT

Young North Bone Spring

23. SEC. T. R. S. OR BLM. AND COUNTY OR AREA

Sec. 17: T18S, R32E

24. COUNTY OR PARISH

Lea

25. STATE

NM

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

REPAIR WELL

(Other)

FILL OR ALTER CASING

MULTIPLE COMPLETES

ABANDON*

CHANGE PLANE

COMPLETION REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) TD & Logging

(NOTE: Report results of multiple completions on Well Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

26. DESCRIBE PROPOSED OR COMPLETED OPERATION (Clearly state all pertinent details and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give substantial locations and measured and true vertical depths for all markers and zones pertinent to this work.)

10/20/88 TD 7 7/8" hole to 9200' @ 12:00 midnight, RU Schlumberger & ran DLL/MSFL & CN/LDT logs on the interval 2402'-9177', loggers TD 9178', SION.

10/21/88 RU Dowell Schlumberger to plug & abandon, set plug @ 9000', cement as follows:

1st stage - 70 sks @ 8842'-9000', tag plug w/wireline @ 8842'
 2nd stage - 44 sks @ 6280'-6380'
 3rd stage - 60 sks @ 2224'-2470', tag plug w/wireline @ 2224'
 4th stage - 30 sks @ 450'-550'
 5th stage - 15 sks @ 0'-50'

Release WEK Rig #1 @ 2:00 AM on 10/23/88.

27. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Drilling/Production Secretary DATE 11/15/88

(This space for Federal or State other use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

Approved as to plugging of the well bore,
 integrity under bond is retained until
 surface restoration is completed.

*See Instructions on Reverse Side

PA posted 10/1/88

Received

DEC 5 1988

OCD
HOBBS OFFICE