

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N. M. OIL CONS. COMM. JCH
P. O. BOX 1080
HOBBS, NEW MEXICO 88240

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	6. LEASE DESIGNATION AND SERIAL NO. NM-56263
2. NAME OF OPERATOR Manzano Oil Corporation	8. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR P.O. Box 2107, Roswell, NM 88202-2107	7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface Unit 9 1650' FSL & 1650' FEL	9. FARM OR LEASE NAME Sun Pearl Federal
14. PERMIT NO. 30-025-30409	10. WELL NO. #1
15. ELEVATIONS (Show whether DS, ST, GS, etc.) 3700.4 3702' GL	11. FIELD AND POOL, OR WILDCAT Pearl Queen
	12. COUNTY OR PARISH Lea
	13. STATE NM

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF	☐	PEEL OR ALTER CASING	☐
FRACTURE TREAT	☐	MULTIPLE COMPLETE	☐
SHOOT OR ACIDIZE	☐	ABANDON*	☐
REPAIR WELL	☐	CHANGE PLANE	☐
(Other)	☐		☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF	☐	REPAIRING WELL	☐
FRACTURE TREATMENT	☐	ALTERING CASING	☐
SHOOTING OR ACIDIZING	☐	ABANDONMENT*	☒
(Other) Running casing	☐		

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

- 6/04/89 Ran 33 jts (1344.89') 8-5/8" 24# J55 ST&C 8 rnd casing & set @ 1342' with float shoe, float collar & two centralizers. Cemented with 500 sacks Halliburton lite 2% CaCl, and 1/4# floseal. Tail with 200 sacks Class C 2% CaCl. Circulate 280 sacks. PD @ 7:30 p.m. 6/3/89. Test casing to 1000# held ok.
- 6/13/89 Ran 123 jts (5158') 4-1/2" 11.60# J55 casing. Cemented @ 5150' with 1000 sacks Halliburton Lite, 12# salt, 1/4# floseal, 600 sacks 50/50 pozmix, 5# salt, 3/10 of 1% Halide 4, 2/10 of 1% CFR2. PD @ 11:30 p.m. 6/12/89. Circulated cement.

18. I hereby certify that the foregoing is true and correct

SIGNED Allen Wiggins TITLE Land/Drilling Secretary DATE June 30, 1989

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side